

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES								MISSED APPROACH								
FROM		TO		COURSE AND DISTANCE		ALTITUDE										
AGARD WP (IAF)		ZAKLY WP (NoPT) (TF) (FB)		210.34/6.69		2100		LNAV: RW29 CLIMBING RIGHT TURN TO 2100 DIRECT ZAKLY WP AND HOLD ADDITIONAL FLIGHT DATA: FAS OBST: 117' TREE 385903/761933 CHART: 425' TOWER 385732/761530 AZLOM WP TO RW29: 2.91/39@								
HUNNE WP (IAF)		ZAKLY WP (NoPT) (TF) (FB)		023.92/5.00		2100										
ZAKLY WP		AZLOM WP (TF) (FB)		293.99/5.00		1600										
RW29 (MAP)		ZAKLY WP (DF) (FO)				2100										
1. PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE ZAKLY WP, RT, 293.99 INBOUND 2100 FT IN LIEU OF PT (IAF) 3. FAC: 293.93 FAF: AZLOM WP _____ DIST FAF TO MAP: - THLD: 5.00 4. MIN. ALT: ZAKLY 2100, AZLOM 1600, 2.50 NM TO RW29 820 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: _____ 34:1 IS CLEAR 8. MSA FROM: RW29 2600								FINAL SEGMENT: (TF) MAG VAR: 11W EPOCH YEAR: 00								
MINIMUMS																
TAKEOFF: <input checked="" type="checkbox"/> STANDARD		SEE FAA FORM 8260-15 FOR THIS AIRPORT						ALTERNATE: <input type="checkbox"/> NA <input checked="" type="checkbox"/> X								
CATEGORY		A			B			C			D			E		
		DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA		380	1	365	380	1	365		NA			NA				
CIRCLING		460	1	445	480	1	465		NA			NA				
EASTON/NEWNAM FIELD ALTIMETER SETTING MINIMUMS																
LNAV MDA		420	1	405	420	1	405		NA			NA				
CIRCLING		500	1	485	500	1	485		NA			NA				
NOTES: OBTAIN LOCAL ALTIMETER SETTING ON CTAF, WHEN NOT RECEIVED USE EASTON/NEWNAM FIELD ALTIMETER SETTING MINIMUMS. GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA. @ DESCENT ANGLE NA WITH EASTON/NEWNAM ALTIMETER SETTING																
CITY AND STATE		ELEVATION: 15 TDZE: 15		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:						
STEVENSVILLE, MD		BAY BRIDGE		RNAV		RNAV RWY 29, ORIG, OCT 5, 2000				AMDT: NONE						
												DATED:				