

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW20C CLIMB TO 3000 DIRECT JASOP AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 020.94 INBOUND. CHART FAS OBST: 706 TOWER 360903N/0863953W CHART VDP AT 1.01 MILES TO RW20C. MNNKY TO RW20C: 3.00/50. CHART CIRCLING ICON.	
LENON (IAF)	CTHRN (FB)	274.34 / 20.07	3000		
TANDS (IAF)	CTHRN (FB)	192.24 / 15.00	3000		
CTHRN (IF)	MNNKY (FB)	201.03 / 6.10	2000		
MNNKY (FAF)	XEJFY/2.10 NM TO RW20C (FB)	201.01 / 2.23			
XEJFY/2.10 NM TO RW20C	RW20C (MAP) (FO)	201.01 / 2.10			
RW20C (MAP)	960 MSL	201.01			
960 MSL	JASOP (FO)		3000		
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT CTHRN 3. FAF: <u>201.01</u> FAF: <u>MNNKY</u> DIST FAF TO MAP: <u>4.33</u> THLD: <u>4.33</u> 4. MIN. ALT: CTHRN 3000, MNNKY 2000, XEFJY/2.10 NM TO RW20C 1280 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW20C 3100					
				MAG VAR: 3W EPOCH YEAR: 2010	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A		STANDARD @
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	960	1	388	960	1
CIRCLING	1100	1	501	1120	1
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LENON ON V140 EASTBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT TANDS ON V49 NORTHBOUND. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.					
CITY AND STATE		ELEVATION: 599 THRE: 572		FACILITY IDENTIFIER: RNAV	
NASHVILLE, TN		AIRPORT NAME: NASHVILLE INTL		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20C, ORIG-A 24 JULY 2014	
				SUP: AMDT: ORIG DATED 04/05/2012	



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
2
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	LENON	LENON	010	IAF	IF		FB					
	LENON	CTHRN	020		TF		FB	1.0	274.3(271.3T)	020.1	AA 03000	
	TANDS	TANDS	010	IAF	IF		FB					
	TANDS	CTHRN	020		TF		FB	1.0	192.2(189.2T)	015.0	AA 03000	
		CTHRN	010	FACF	IF		FB				AA 03000	
		MNNKY	020	FAF	TF		FB	0.5	201.0(198.0T)	006.1	AA 02000	
		XEFJY	021	SDF	TF		FB	0.3	201.0(198.0T)	002.2	AA 01280 GS 01291	
		RW20C	030	MAP	TF		FO	0.3	201.0(198.0T)	002.1	AT 00622	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		201.0(198.0T)		AA 00960	
	JASOP	050		DF		FO				AA 03000	
	JASOP	060		HM	R	FO		020.9(017.9T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CTHRN	N361723.22	W0863647.47	N3617.387	W08636.791
	JASOP	N355452.93	W0864547.54	N3554.882	W08645.792
	LENON	N361657.51	W0861158.33	N3616.959	W08611.972
	MNNKY	N361134.55	W0863907.47	N3611.576	W08639.125
	TANDS	N363212.96	W0863348.65	N3632.216	W08633.811
	XEFJY	N360927.25	W0863958.49	N3609.454	W08639.975
	RW20C	N360727.24	W0864046.55	N3607.454	W08640.776

RUNWAY DATA	THRESHOLD	
RWY	ELEVATION	TCH
RW20C	00572	50

QUALITY
2
CHECKED

CITY AND STATE NASHVILLE, TN	ELEVATION: 599 THRE: 572	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: NASHVILLE INTL	RNAV	RNAV (GPS) RWY 20C, ORIG-A 24 JULY 2014	AMDT: ORIG
				DATED: 04/05/2012