

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH											
FROM			TO			COURSE AND DISTANCE				ALTITUDE		MAP: 4.90 MILES AFTER HADIT INT/14.39 DME									
CHQ NDB CGI VOR/DME (IF)			CGI VOR/DME HADIT INT/CGI 14.39 DME			337.74 / 25.15 179.93 / 14.39				3500 2100		CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 3500 DIRECT CHQ NDB AND HOLD, CONTINUE CLIMB IN HOLD TO 3500. ADDITIONAL FLIGHT DATA: HOLD S, RT, 009.00 INBOUND. FAS OBST: 554 AAO 365738N/0893312W HADIT TO RW20: 3.35/45. CHART CIRCLING ICON									
1. PT <u> L </u> SIDE OF COURSE <u> 359.93 </u> OUTBOUND <u> 3500 </u> FT WITHIN <u> 10 </u> MILES OF <u> CGI VOR/DME </u> (IAF) 2. _____ 3. FAC <u> 179.93 </u> FAF <u> HADIT INT/CGI 14.39 DME </u> DIST FAF TO MAP <u> 4.90 </u> THLD <u> 4.90 </u> 4. MIN. ALT <u> CGI VOR/DME 3500, HADIT 2100 </u> 8. MSA FROM: <u> CGI VOR/DME 090-180 3000, 180-270 2200, 270-090 3500 </u>										MAG VAR: 2W EPOCH YEAR: 2015											
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X											
CATEGORY =====>		A			B			C			D			E							
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA						
S-20	820	1	506	820	1	506	820	1 3/8	506	820	1 3/8	506									
CIRCLING	840	1	525	860	1	545	1080	2 1/4	765	1160	2 3/4	845									
NOTES: CHART NOTE: ADF REQUIRED. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON CGI VOR/DME AIRWAY RADIALS 312 CW 042. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CAPE GIRARDEAU ALTIMETER SETTING AND (SEE FORM 8260-10)																					
CITY AND STATE SIKESTON, MO				ELEVATION: 315 THRE: 314				FACILITY IDENTIFIER: CGI		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 20, AMDT 4, 06/27/2013				SUP							
				AIRPORT NAME:										AMDT 3C							
				SIKESTON MEMORIAL MUNI										DATE 09/28/2006							


VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 60 FEET AND S-20 CAT C/D AND CIRCLING CAT C/D VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.



CITY AND STATE

SIKESTON, MO

ELEVATION: 315

THRE: 314

AIRPORT NAME:

SIKESTON MEMORIAL MUNI

FACILITY
IDENTIFIER:

CGI

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 20, AMDT 4, 06/27/2013

SUP:

AMDT:

3C

DATED:

09/28/2006