

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW16						
EJKAX (IF/IAF)		AYDOV (TF) (FB) (RNP 1.00)		157.60 / 6.03				2700		CLIMB TO 3000 DIRECT JODIV AND HOLD.						
AYDOV (FAF)		ZUVKO/1.90 NM TO RW16 (TF) (FB) (RNP 0.30)		157.63 / 3.25												
ZUVKO/1.90 NM TO RW16		RW16 (MAP) (TF) (FO) (RNP 0.30)		157.63 / 1.90						ADDITIONAL FLIGHT DATA: HOLD S, RT, 337.73 INBOUND. CHART FAS OBST: 1098 TOWER 404118N/0925349W DISTANCE TO THLD FROM 250 HAT: 0.67 NM. CHART VDP AT 0.94 NM TO RW16* *LNAV ONLY. WAAS CHANNEL # 70440 REFERENCE PATH ID: W16A CHART CHART CIRCLING ICON. LTP HAE: 279 M						
RW16 (MAP)		1273 MSL		157.63												
1273 MSL		JODIV (DF) (FO) (RNP 1.00)						3000								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD N EJKAX, RT, 157.60 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC: 157.63 FAF: _____ DIST FAF TO MAP: 5.15 THLD: 5.15																
4. MIN. ALT: EJKAX 3000, AYDOV 2700, ZUVKO/1.90 NM TO RW16 1660*																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: 2700 GS ALT AT: AYDOV 2700 OM: _____ MM: _____ IM: _____																
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR																
8. MSA FROM: _____																
MAG VAR: 1E EPOCH YEAR: 2010																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @				
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1273	1	250	1273	1	250		NA			NA					
LNAV/VNAV DA	1273	1	250	1273	1	250		NA			NA					
LNAV MDA	1360	1	337	1360	1	337		NA			NA					
CIRCLING																
	1420	1	397	1480	1	457		NA			NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 16 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING CHARITON ALTIMETER SETTING. (CONTINUED ON PAGE 2)																
CITY AND STATE CENTERVILLE, IA		ELEVATION: 1023 TDZE: 1023 AIRPORT NAME: CENTERVILLE MUNI				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 1 2 MARCH 2017				SUP: AMDT: ORIG DATED 06/03/2010				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARITON ALTIMETER SETTING AND INCREASE ALL DA 71 FEET AND ALL VISIBILITIES 1/8 SM AND ALL MDA 80 FEET.

TAA

	FROM	TO	ALT
1.	068/30 CW 248/30 (NOPT)	EJKAX (IF/IAF) (FB)	3000
2.	248/30 CW 068/30	EJKAX (IF/IAF) (FO)	3000

QUALITY
16
CHECKED

CITY AND STATE
CENTERVILLE, IA

ELEVATION: 1023 TDZE: 1023
AIRPORT NAME:
CENTERVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, AMDT 1
2 MARCH 2017

SUP:
AMDT: ORIG
DATED: 06/03/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KTVK
RUNWAY	RW16
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W16A
LTP/FTP LATITUDE	404122.8040N
LTP/FTP LONGITUDE	0925413.2595W
LTP/FTP ELLIPSOIDAL HEIGHT	+02790
FPAP LATITUDE	403959.7570N
FPAP LONGITUDE	0925330.6510W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1504
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

A8EE03D0

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+03111
FPAP ORTHOMETRIC HEIGHT	+03111

QUALITY
16
CHECKED

CITY AND STATE CENTERVILLE, IA	ELEVATION: 1023 TDZE: 1023 AIRPORT NAME: CENTERVILLE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 1 2 MARCH 2017	SUP:
				AMDT: ORIG
				DATED: 06/03/2010