

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ICT VORTAC	SEZER/ICT 23.00 DME/RADAR	094.94 / 23.00	3600	MAP: 5.18 MILES AFTER SEZER/ICT 23.00 DME/RADAR OR AT ICT 17.82 DME FIX CLIMBING RIGHT TURN TO 3000 ON ICT VORTAC R-095 TO SEZER/ICT 23.00 DME/RADAR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 274.94 INBOUND. FAS OBST: 1579 AAO 374207N/0970823W FAC CROSSES RWY 01 THLD. CHART CIRCLING ICON.

1. PT L SIDE OF COURSE 094.94 OUTBOUND 3000 FT WITHIN 10 MILES OF SEZER (IAF)
2.
3. FAC 274.94 FAF SEZER/ICT 23.00 DME/RADAR DIST FAF TO MAP 5.18 THLD
4. MIN. ALT SEZER 2900
8. MSA FROM: ICT VORTAC 4000

MAG VAR: 7E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1840	1	431	2120	1	711	2120	2	711	2120	2 1/4	711			

NOTES:

CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE WICHITA MID-CONTINENT ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET AND INCREASE CAT C AND D VISIBILITY 1/4 MILE.
CHART PLANVIEW NOTE: RADAR OR DME REQUIRED.

QUALITY
2
REVIEWED

CITY AND STATE WICHITA, KS	ELEVATION: 1409 AIRPORT NAME: BEECH FACTORY	TDZE:	FACILITY IDENTIFIER: ICT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR-B, AMDT 4 25 JULY 2013	SUP 3 DATE 03/15/2007
--------------------------------------	--	-------	------------------------------------	---	---