

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA	FROM	TO	ALT
1.	106/30 CW 136/30 (NOPT)	106/20 CW 136/20	4100
2.	106/20 CW 136/20	ACUBO (IF/IAF) (FB)	3600
	136/30 CW 286/30 (NOPT)	ACUBO (IF/IAF) (FB)	3600
3.	286/30 CW 016/30	BEBAC (IAF) (FB)	3600
4.	016/30 CW 106/30	CADAC (IAF) (FB)	3600

QUALITY
6
CHECKED

CITY AND STATE
WICHITA, KS

ELEVATION: 1333 TDZE: 1330
AIRPORT NAME:
WICHITA DWIGHT D. EISENHOWER NATIONAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Y RWY 19R, AMDT 1A
13 NOVEMBER 2014

SUP:
AMDT: 1
DATED: 09/23/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KICT
RUNWAY	RW19R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W19A
LTP/FTP LATITUDE	373941.7630N
LTP/FTP LONGITUDE	0972601.7925W
LTP/FTP ELLIPSOIDAL HEIGHT	+03765
FPAP LATITUDE	373806.0670N
FPAP LONGITUDE	0972645.5905W
THRESHOLD CROSSING HEIGHT (TCH)	00052.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

35899C8E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+04053
FPAP ORTHOMETRIC HEIGHT	+04053

QUALITY
6
CHECKED

CITY AND STATE

WICHITA, KS

ELEVATION: 1333

TDZE: 1330

AIRPORT NAME:

WICHITA DWIGHT D. EISENHOWER NATIONAL

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Y RWY 19R, AMDT 1A

13 NOVEMBER 2014

SUP:

AMDT: 1


DATED: 09/23/2010

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
6
CHECKED

Page 4 of 5 Pages

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ACUBO	ACUBO	010	IAF	HF	R	FO		196.1 (200.1T)	004.0	AA 03600	
	BEBAC	BEBAC	010	IAF	IF		FB					
	BEBAC	ACUBO	020		TF		FB	1.0	286.1 (290.1T)	006.0	AA 03600	
	CADAC	CADAC	010	IAF	IF		FB					
	CADAC	ACUBO	020		TF		FB	1.0	106.0 (110.0T)	006.0	AA 03600	
		ACUBO	010	FACF	IF		FB				AA 03600	
		BAYCO	020	FAF	TF		FB	0.5	196.1 (200.1T)	006.1	AA 03000	
		WABOV	021	SDF	TF		FB	0.3	196.0 (200.0T)	002.0	AA 02340	GS 02346
		RW19R	030	MAP	TF		FO	0.3	196.0 (200.0T)	003.0	AT 01382	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		196.0 (200.0T)		AA 01530	
		CUTIK	050		DF		FO				AA 03600	
		CUTIK	060		HM	R	FO		016.0 (020.0T)	004.0	AA 03600	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		ACUBO	N375008.22		W0972114.25		N3750.137		W09721.238			
		BAYCO	N374424.60		W0972352.15		N3744.410		W09723.869			
		BEBAC	N374804.44		W0971407.55		N3748.074		W09714.126			
		CADAC	N375211.57		W0972821.34		N3752.193		W09728.356			
		CUTIK	N372741.47		W0973130.74		N3727.691		W09731.512			
		WABOV	N374231.09		W0972444.21		N3742.518		W09724.737			
		RW19R	N373941.76		W0972601.79		N3739.696		W09726.030			
RUNWAY DATA			THRESHOLD									
	RWY	ELEVATION		TCH								
	RW19R	01330		52								



CITY AND STATE WICHITA, KS	ELEVATION: 1333	TDZE: 1330	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: WICHITA DWIGHT D. EISENHOWER NATIONAL		RNAV	RNAV (GPS) Y RWY 19R, AMDT 1A 13 NOVEMBER 2014	AMDT: 1
					DATED: 09/23/2010