

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.12 MILES AFTER PICHE LOM						
ICT VORTAC		PICHE LOM		141.62 / 11.72				3600		CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 3000 DIRECT PICHE LOM AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 016.01 INBOUND. CHART FAS OBST: 1433 ELEV 373529N/0972617W PICHE LOM TO RW01R: 3.03/54.						
1. PT <u> L </u> SIDE OF COURSE <u> 196.01 </u> OUTBOUND <u> 3000 </u> FT WITHIN <u> 10 </u> MILES OF <u> PICHE LOM </u> (IAF) 2. _____ 3. FAC <u> 016.01 </u> FAF <u> PICHE LOM </u> DIST FAF TO MAP <u> 4.12 </u> THLD <u> 4.12 </u> 4. MIN. ALT <u> PICHE LOM 2700 </u> 8. MSA FROM: <u> IC LOM 3600 </u>										MAG VAR: 4E EPOCH YEAR: 2015						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-01R	1740	4000	419	1740	4000	419	1740	4000	419	1740	5000	419				
CIRCLING	1800	1	467	1800	1	467	1800	1 1/2	467	1900	2	567				
NOTES: CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-1R CAT C VISIBILITY TO RVR 5000.																
CITY AND STATE		ELEVATION: 1333 TDZE: 1321		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP						
WICHITA, KS		AIRPORT NAME:		IC		NDB RWY 1R, AMDT 15C 13 NOVEMBER 2014				AMDT 15B						
		WICHITA DWIGHT D. EISENHOWER NATIONAL								DATE 03/18/2003						