

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES								MISSED APPROACH			
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LNAV: RW35 CLIMB TO 3300 DIRECT OMEHI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 176.00 INBOUND. FAS OBST: 1882 AAO 435333N/0954814W APEWO TO RW35: 3.00/40. CHART CIRCLING ICON.			
JEYZO (IF/IAF)		APEWO (FB)		356.00 / 4.86		3300					
APEWO (FAF)		RW35 (MAP) (FO)		356.00 / 5.14							
RW35 (MAP)		2023 MSL		356.00							
2023 MSL		OMEHI (FO)				3300					

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)							
2. HOLD S JEYZO, RT, 356.00 INBOUND, 3400 FT. IN LIEU OF PT (IAF)							
3. FAC: 356.00 FAF: APEWO DIST FAF TO MAP: 5.14 THLD: 5.14							
4. MIN. ALT: JEYZO 3400, APEWO 3300							
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>							
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>							
7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR							
8. MSA FROM: <u> </u>							
MAG VAR: 4E EPOCH YEAR: 2000							

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @			
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2140	1	517	2140	1	517		NA			NA				
CIRCLING	2140	1	517	2300	1	677		NA			NA				

NOTES:
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRACY MUNI ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE SLAYTON, MN		ELEVATION: 1623 THRE: 1623 AIRPORT NAME: SLAYTON MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 22 AUGUST 2013		SUP: AMDT: NONE DATED	
-------------------------------	--	---	--	------------------------------	--	---	--	-----------------------------	--

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	266/30 CW 086/30 (NOPT)	JEYZO (IF/IAF) (FB)	3400
2.	086/30 CW 266/30	JEYZO (IF/IAF) (FO)	3900

QUALITY
CHECKED

CITY AND STATE

SLAYTON, MN

ELEVATION: 1623

THRE: 1623

AIRPORT NAME:

SLAYTON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG

22 AUGUST 2013

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KDVPK3FR35	AJEYZO	010JEYZOK3EA0EE	AR	HF		35600040	+	03400	18000		B	JS
SUSAP	KDVPK3FR35	R	010JEYZOK3EA0E	I	IF			+	03400	18000		B	JS
SUSAP	KDVPK3FR35	R	020APEWOK3EA1E	F	051TF		35600049	+	03300			B	JS
SUSAP	KDVPK3FR35	R	020APEWOK3EA2WN			N	ALNAV						JS
SUSAP	KDVPK3FR35	R	030RW35 K3PGOGY	M	031TF		35600051		01663	-300		B	JS
SUSAP	KDVPK3FR35	R	040		0 M	CA	3560	+	02023			B	JS
SUSAP	KDVPK3FR35	R	0500MEHIK3EA0EY		DF			+	03300			B	JS
SUSAP	KDVPK3FR35	R	0600MEHIK3EA0EE	R	HM		17600040	+	03300			B	JS

QUALITY
4
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	JEYZO	JEYZO	010	IAF	HF	R	FO		356.0 (360.0T)	004.0	AA 03400	
		JEYZO	010	FACF	IF		FB				AA 03400	
		APEWO	020	FAF	TF		FB	0.5	356.0 (360.0T)	004.9	AA 03300	
		RW35	030	MAP	TF		FO	0.3	356.0 (360.0T)	005.1	AT 01663	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		356.0 (360.0T)		AA 02023	
	OMEHI	050		DF		FO				AA 03300	
	OMEHI	060		HM	R	FO		176.0 (180.0T)	004.0	AA 03300	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	APEWO	N435349.19	W0954657.40	N4353.820	W09546.957
	JEYZO	N434857.59	W0954657.40	N4348.960	W09546.957
	OMEHI	N440937.55	W0954657.40	N4409.626	W09546.957
	RW35	N435857.64	W0954657.40	N4358.961	W09546.957

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	01623	40

QUALITY
A
CHECKED

CITY AND STATE SLAYTON, MN	ELEVATION: 1623	THRE: 1623	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 22 AUGUST 2013	SUP:
	AIRPORT NAME: SLAYTON MUNI				AMDT: NONE
					DATED: