

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>NDB STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - FAR PART 97.27</b>										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>									
FROM			TO			COURSE AND DISTANCE				ALTITUDE			MAP: ATK NDB						
MEADE INT/BRW 40.00 DME			ATK NDB			135.15 / 14.33				2000			CLIMB TO 1600 THEN CLIMBING RIGHT TURN TO 2000 DIRECT ATK NDB AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD E, RT, 248.69 INBOUND. FAS OBST: 320 AAO 703023N/1571020W FAC CROSSES RWY C/L EXTENDED 2993 FROM THLD.						
1. PT <u>R</u> SIDE OF COURSE <u>068.69</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF <u>ATK NDB</u> (IAF) 2. _____ 3. FAC <u>248.69</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: ATK NDB 1500										MAG VAR: 20E EPOCH YEAR: 2005									
<b>MINIMUMS</b>																			
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @							
CATEGORY >>>>>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-24		680	1	584	680	1	584	680	1 1/2	584		NA							
CIRCLING		680	1	584	680	1	584	680	1 1/2	584		NA							
NOTES:  CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BARROW ALTIMETER SETTING AND INCREASE ALL MDA 140 FEET AND ALL CAT C VISIBILITIES 1/2 MILE.																			
CITY AND STATE  ATQASUK, AK		ELEVATION: 96 TDZE: 96 AIRPORT NAME:  ATQASUK EDWARD BURNELL SR MEMORIAL		FACILITY IDENTIFIER:  ATK		PROCEDURE NO./AMD T NO./EFFECTIVE DATE:  NDB RWY 24, AMDT 2  29 JUL 2010						SUP							
												AMDT 1							
												DATE 03/15/2007							