

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW20 CLIMBING LEFT TURN TO 4000 DIRECT DOYEV AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1779 TREES 384446N/0803847W FORIV TO RW20: 3.00/40.0. CHART CIRCLING ICON.									
DOYEV (IF/IAF)		FORIV (FB)		195.72 / 5.96				3000											
FORIV (FAF)		RW20 (MAP) (FO)		195.71 / 5.29															
RW20 (MAP)		1676 MSL		195.71				4000											
1676 MSL		DOYEV (FO)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N DOYEV, RT, 195.72 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: 195.71 FAF: FORIV DIST FAF TO MAP: 5.29 THLD: 5.29 4. MIN. ALT: DOYEV 4000, FORIV 3000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 8W		EPOCH YEAR: 2015	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		<input checked="" type="checkbox"/> X							
CATEGORY =====>		A		B		C		D		E									
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LNAV MDA	2060	1	784	2060	1 1/4	784	2060	2 1/2	784		NA								
CIRCLING	2060	1	784	2240	1 1/2	964	2240	3	964		NA								
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. (SEE FORM 8260-10)																			
CITY AND STATE		ELEVATION: 1276 TDZE: 1276		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP: RNAV (GPS) RWY 19									
SUTTON, WV		AIRPORT NAME: BRAXTON COUNTY				RNAV (GPS) RWY 20, AMDT 1 8 JANUARY 2015				AMDT: ORIG									
										DATED 12/22/2005									



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLARKSBURG ALTIMETER SETTING AND INCREASE ALL MDA 260 FT. INCREASE LNAV CAT A/B VISIBILITY 1/4 MILE, LNAV CAT C VISIBILITY 1/2 MILE, AND CIRCLING CAT A VISIBILITY 1/4 MILE.

TAA	FROM	TO	ALT
1.	106/30 CW 286/30 (NOPT)	106/15 CW 286/15	5300
2.	106/15 CW 286/15	DOYEV (IF/IAF) (FB)	4000
3.	286/30 CW 106/30	286/13 CW 106/13	5900
4.	286/13 CW 106/13	DOYEV (IF/IAF) (FO)	4000

QUALITY
5
CHECKED

CITY AND STATE
SUTTON, WV

ELEVATION: 1276 TDZE: 1276
AIRPORT NAME:
BRAXTON COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 20, AMDT 1
8 JANUARY 2015

SUP: RNAV (GPS) RWY 19
AMDT: ORIG
DATED: 12/22/2005

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
5
CHECKED

CITY AND STATE SUTTON, WV	ELEVATION: 1276	TDZE: 1276	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 19
	AIRPORT NAME:			RNAV (GPS) RWY 20, AMDT 1	AMDT: ORIG
	BRAXTON COUNTY		RNAV	8 JANUARY 2015	DATED: 12/22/2005

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	DOYEV	DOYEV	010	IAF	HF	R	FO		195.7 (187.7T)	004.0	AA 04000	
		DOYEV	010	FACF	IF		FB				AA 04000	
		FORIV	020	FAF	TF		FB	0.5	195.7 (187.7T)	006.0	AA 03000	
		RW20	030	MAP	TF		FO	0.3	195.7 (187.7T)	005.3	AT 01316	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		195.7 (187.7T)		AA 01676	
	DOYEV	050		DF	L	FO				AA 04000	
	DOYEV	060		HM	R	FO		195.7 (187.7T)	004.0	AA 04000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DOYEV	N385242.67	W0803708.32	N3852.711	W08037.139
	FORIV	N384647.91	W0803809.75	N3846.799	W08038.163
	RW20	N384133.12	W0803904.13	N3841.552	W08039.069

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW20	01276	40

QUALITY
5
CHECKED

CITY AND STATE SUTTON, WV	ELEVATION: 1276	TDZE: 1276	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1 8 JANUARY 2015	SUP: RNAV (GPS) RWY 19
	AIRPORT NAME: BRAXTON COUNTY				AMDT: ORIG
					DATED: 12/22/2005