

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: OSH VORTAC					
										CLIMB TO 3000 ON OSH VORTAC R-270.00 TO GRATE INT/OSH 8.71 DME AND HOLD.					
										ADDITIONAL FLIGHT DATA: HOLD W, RT, 090.00 INBOUND. FAS OBST: 979 AAO 435854N/0881929W CHART VDP AT 1.66 DME; DISTANCE VDP TO THLD 1.43 MILES. CHART CIRCLING ICON FAC CROSSES RWY C/L EXTENDED 5027 FROM THLD.					
1. PT <u>R</u> SIDE OF COURSE <u>085.00</u> OUTBOUND <u>2600</u> FT WITHIN <u>10</u> MILES OF <u>OSH VORTAC</u> (IAF) 2. _____ 3. FAC <u>265.00</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: <u>OSH VORTAC 2700</u>										MAG VAR: 2E		EPOCH YEAR: 1965			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N/A				STANDARD @							
CATEGORY =====>		A		B		C		D		E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-27	1280	1	502	1280	1	502	1280	1 3/8	502	1280	1 3/8	502			
CIRCLING	1280	1	472	1300	1	492	1360	1 1/2	552	1440	2	632			
NOTES: CHART NOTE: CIRCLING TO RWY 5, 23, AND 31 NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FOND DU LAC ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET; INCREASE S-27 CATS C AND D VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/8 MILE, AND CAT D 1/4 MILE. (SEE FORM 8260-10)															
CITY AND STATE				ELEVATION: 808 THRE: 778		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP			
OSHKOSH, WI				AIRPORT NAME:		OSH		VOR RWY 27, AMDT 5 22 AUGUST 2013				AMDT 4C			
				WITTMAN RGNL								DATE 03/10/2011			



VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VDP NA WITH FOND DU LAC ALTIMETER SETTING.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

QUALITY
6
CHECKED

CITY AND STATE

OSHKOSH, WI

ELEVATION: 808

THRE: 778

AIRPORT NAME:

WITTMAN RGNL

FACILITY
IDENTIFIER:

OSH

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

VOR RWY 27, AMDT 5

22 AUGUST 2013

SUP:

AMDT: 4C

DATED: 03/10/2011