

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: EVUCI
FOLEL (IAF)	ROCES (NOPT) (FB)	155.44 / 5.00	2000	CLIMB TO 2000 DIRECT NEGIE AND HOLD.
UCUBA (IAF)	ROCES (NOPT) (FB)	335.42 / 5.00	2000	
ROCES (IF/IAF)	NAKEK (FB)	065.42 / 6.17	1600	
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 246.47 INBOUND. CHART FAS OBST: 207 TOWER 700735N/1433718W CHART VDP AT 1.01 MILES TO EVUCI. NAKEK TO RW07: 3.04/38. ROUTE TYPE DESCRIPTION: A, P APPROACH ROUTE QUALIFIER 2: S

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD SW ROCES, RT, 065.42 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
- FAC: 065.71 FAF: NAKEK DIST FAF TO MAP: 4.33 THLD: 4.83
- MIN. ALT: ROCES 2000, NAKEK 1600
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 27E

EPOCH YEAR: 2005

**MINIMUMS**

TAKEOFF:	X	STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD						
CATEGORY		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA		520	1	518	520	1	518	520	1 1/2	518	520	1 3/4	518			
CIRCLING		560	1	558	560	1	558	560	1 1/2	558	560	2	558			

NOTES:  
CHART NOTE: DME/DME RNP-0.3 NA.

CITY AND STATE  
BARTER ISLAND, AK

ELEVATION: 2 TDZE: 2  
AIRPORT NAME:  
BARTER ISLAND LRRS

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 7, ORIG  
NOV 23 2006

SUP:  
AMDT: NONE  
DATED

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA	FROM	TO	ALT
1.	335/30 CW 043/30	335/18 CW 043/18	6700
2.	335/18 CW 043/18 (NOPT)	ROCES (IF/IAF)	2000
	043/30 CW 155/30 (NOPT)	ROCES (IF/IAF)	2000
3.	155/30 CW 245/30	FOLEL (IAF)	2000
4.	245/30 CW 335/30	245/13 CW 335/13	4600
5.	245/13 CW 335/13	UCUBA (IAF)	2000

CITY AND STATE

BARTER ISLAND, AK

ELEVATION: 2 TDZE: 2

AIRPORT NAME:

BARTER ISLAND LRRS

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./ EFFECTIVE DATE:

RNAV (GPS) RWY 7, ORIG

NOV 23 2006

SUP:

AMDT: NONE

DATED: