

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/1/08	MI	Saginaw	Saginaw County H.W. Browne	8/5479	5/8/08	RNAV (GPS) RWY 9, Orig

FDC **8/5479** HYX FI/P SAGINAW COUNTY H.W. BROWNE, SAGINAW, MI. RNAV (GPS) RWY 9, ORIG...CIRCLING: VIS CAT A 1, CAT B 1-1/4. TERMINAL ROUTE FLINT (FNT) VORTAC TO SEGOY MINIMUM ALTITUDE 2900. DELETE NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE SAGINAW MBS INTL ALTIMETER SETTING AND INCREASE ALL DA S/MDA S 40 FEET. DELETE NOTE: BARO-VNAV NA BELOW -16C(4F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SAGINAW MBS INTL ALTIMETER SETTING AND INCREASE ALL DA 36 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS VIS 1/4 MILE, INCREASE ALL MDA 40 FEET, INCREASE LNAV VIS CAT C 1/4 MILE AND CIRCLING VIS CAT C 1/4 MILE. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEM, PROCEDURE NA BELOW -16C(4F) OR ABOVE 47C(116F). THIS IS RNAV (GPS) RWY 9, ORIGA.