

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: TRX NDB							
JAWED INT		TRX NDB		079.14 / 20.28				2500		CLIMB TO 2200, THEN CLIMBING RIGHT TURN TO 2500 DIRECT TRX NDB AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, LT, 183 INBOUND. FAS OBST: 1078 TREE 401248 / 933245 FAC 304R OF RWY C/L EXTENDED 3000 FROM THLD.							
IRK VORTAC		TRX NDB		260.25 / 46.21				2600									
LMN VORTAC		TRX NDB		143.85 / 35.42				2700									
UTICA INT		TRX NDB		345.11 / 20.12				2500									
1. PT <u>R</u> SIDE OF COURSE <u>002.61</u> OUTBOUND <u>2500</u> FT WITHIN <u>10</u> MILES OF <u>TRX NDB</u> (IAF) 2. _____ 3. FAC <u>182.61</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: <u>TRX NDB 2600</u>														MAG VAR: 3E		EPOCH YEAR: 00	
MINIMUMS																	
TAKEOFF:		STANDARD		<input checked="" type="checkbox"/>		SEE FAA FORM 8260-15 FOR THIS AIRPORT				ALTERNATE: N		<input checked="" type="checkbox"/>					
CATEGORY		A			B			C			D			E			
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-18		1480	1	724	1480	1	724		NA			NA					
CIRCLING		1480	1	723	1480	1	723		NA			NA					
NOTES: USE CHILLICOTHE MUNI ALTIMETER SETTING.																	
CITY AND STATE				ELEVATION: 757 TDZE: 756		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:						SUP			
TRENTON, MO				TRENTON MUNI		TRX		NDB RWY 18, AMDT 7						AMDT 6A			
														DATED 09/06/91			