

U.S. Department of Transportation
Federal Aviation Administration

RNAV STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Deviations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	T O	COURSE AND DISTANCE	ALTITUDE				
FAPUP WP (IAF) ✓	GISPE WP (NoPT) (TF) (FB) ✓	120.19 / 5.00 ✓	3200 ✓	LNAV-RW21 ✓			
HADPA WP (IAF) ✓	GISPE WP (NoPT) (TF) (FB) ✓	300.33 / 5.00 ✓	3200 ✓	CLIMB TO 3000 DIRECT CESTU WP AND HOLD. ✓			
GISPE WP (FAAF) ✓	HENIS WP (TF) (FB) ✓	210.26 / 5.00 ✓	2500 ✓				
RW21 (MAP)	CESTU WP (DF) (FO)		3000				
				ADDITIONAL FLIGHT DATA: HOLD SW, RT, 030.11 INBOUND ✓ FAS OBS: 996' TREE 425857 / 884724 ✓ CHART: 1059 TOWER 430036 / 884805 ✓ HENIS TO RW21 3.04 / 45 ✓ FINAL SEGMENT: (TF) ✓			
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD NE GISPE WP, RT, 210.23 INBOUND, 3200 FT, IN LIEU OF PT (IAF) ✓ 3. FAC: 210.23 / FAF: HENIS WP DIST FAF TO MAP: THLD: 6.15 ✓ 4. MIN. ALT: GISPE WP 3200, HENIS WP 2500, AVUME WP / 2.30NM 1590 ✓ 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: GS ALT AT: OM: MM: IM: 7. GS ANGLE: TCH: 34:1 IS NOT CLEAR ✓ 8. MSA FROM:							
MAG VAR: 2W EPOCH YEAR: 00 ✓							
MINIMUMS							
TAKEOFF: X STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A X				
CATEGORY	A		B		C		D
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
LNAV MDA	1300	1	500	1300	1	500	NA
CIRCLING	1400	1	600	1400	1	600	NA
NOTES: USE WATERTOWN MUNI ALTIMETER SETTING. GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.							
CITY AND STATE	ELEVATION: 600 TDZE: 800		FACILITY IDENTIFIER: RNAV		PROCEDURE NO. / AMOT NO. / EFFECTIVE DATE: MAY 15 2003		SUP: NONE
FORT ATKINSON, WI	FORT ATKINSON MUNI				RNAV (GPS) RWY 21, ORIG		DATED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV **STANDARD INSTRUMENT APPROACH PROCEDURE**
 FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and IVA. Altitudes are minimum altitudes unless otherwise indicated. Callouts are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.

FROM	TO	ALTITUDE
TAA:		
1. 120/30 CW 300/30 ✓	GISPE WP IF (IAF) (NoPT) ✓	3200 ✓
2. 300/30 CW 030/30 ✓	HADPA WP (IAF) ✓	3200 ✓
3. 030/30 CW 120/30 ✓	FAPUP WP (IAF) ✓	3200 ✓

CITY AND STATE FORT ATKINSON, WI	ELEVATION: 800 TDZE: 800	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: MAY 15 2003 RNAV (GPS) RWY 21, ORIG	SUP:
	AIRPORT NAME: FORT ATKINSON MUNI			AMDT: NONE
				DATED: