

U.S. Department of Transportation
Federal Aviation Administration

**RNAV STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except legibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
DESQE WP (IAF) ✓	CEBTU WP (NoPT) (TF) (FB) ✓	120.04 / 5.00 ✓	3000 ✓	LNAV: RW03 ✓			
ESQGE WP (IAF) ✓	CEBTU WP (NoPT) (TF) (FB) ✓	300.18 / 5.00 ✓	3000 ✓	CLIMB TO 3200 DIRECT GISPE WP AND HOLD. ✓			
CEBTU WP (IF/IAF) ✓	HEMUL WP (TF) (FB) ✓	030.11 / 5.00 ✓	2500 ✓				
RW03 (MAP)	GISPE WP (DF) (FO)		3200				
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 210.23 INBOUND ✓ FAS OBST: 1052' TREE 425720 / 885014 ✓ CHART: 1078 TREE 425360 / 885140 ✓			
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD SW CEBTU WP, RT, 030.11 INBOUND, 3000 FT, IN LIEU OF PT (IAF) ✓ 3. FAC: 030.14, FAF: HEMUL WP DIST FAF TO MAP: - THLD: 5.14 ✓ 4. MIN. ALT: CEBTU WP 3000, HEMUL WP 2500, JAREB WP / 3.00NM 1800 ✓ 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: GS ALT AT: OM: MM: IM: 7. GS ANGLE: TCH: 34:1 IS CLEAR ✓ 8. MSA FROM:				HEMUL TO RW03 3.05 / 40 ✓ FINAL SEGMENT: (TF) ✓ MAG VAR: 2W ✓ EPOCH YEAR: 00 ✓			
MINIMUMS							
TAKEOFF: X STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A X				
CATEGORY	A		B		C		E
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
LNAV MDA	1340	1	540	1340	1	540	1340
CIRCLING	1400	1	800	1400	1	800	1400
NOTES: USE WATERTOWN MUNI ALTIMETER SETTING. ✓ GPS OR RNP-0.3 REQUIRED. OME/OME RNP-0.3 NA. ✓							
CITY AND STATE	ELEVATION: 800 TDZE: 800	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: MAY 15 2003			SUP: NONE	
FORT ATKINSON, WI	FORT ATKINSON MUNI		RNAV (GPS) RWY 3, ORIG			DATED	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FROM

TO

ALTITUDE

TAA:

1. 300/30 CW 120/30 ✓

CEBTU WP IF (IAF) (NoPT) ✓

3500 ✓

2. 120/30 CW 210/30 ✓

DESGE WP (IAF) ✓

3500 ✓

3. 210/30 CW 300/30 ✓

ESOGW WP (IAF) ✓

3500 ✓

CITY AND STATE

FORT ATKINSON, WI

ELEVATION:

800 TDZE:

800

AIRPORT NAME:

FORT ATKINSON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

MAY 15 2003

RNAV (GPS) RWY 3, ORIG

SUP:

AMDT: NONE

DATED: