

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE				ALTITUDE			MAP: MIE VOR/DME						
													CLIMB TO 2200 THEN CLIMBING LEFT TURN TO 2600 DIRECT MIE VOR/DME AND HOLD.						
													ADDITIONAL FLIGHT DATA: HOLD N, RT, 201.05 INBOUND. CHART FAS OBST: 1131 TOWER 401642N/0852052W CHART VDP AT 2.21 DME; DISTANCE VDP TO THLD 1.46 MILES. FAC CROSSES RWY C/L EXTENDED 3001 FROM THLD.						
1. PT <u>L</u> SIDE OF COURSE <u>021.05</u> OUTBOUND <u>2500</u> FT WITHIN <u>10</u> MILES OF <u>MIE VOR/DME</u> (IAF) 2. _____ 3. FAC <u>201.05</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u>DUNKI INT/MIE 3.00 DME 1500*</u> 8. MSA FROM: <u>MIE VOR/DME 2900</u>										MAG VAR: <u>3W</u> EPOCH YEAR: <u>1985</u>									
MINIMUMS																			
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT					ALTERNATE: N A		STANDARD @						
CATEGORY ==>		A			B			C			D			E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-20	1500	1	565	1500	1	565	1500	1 1/2	565	1500	1 3/4	565							
CIRCLING	1500	1	563	1500	1	563	1500	1 1/2	563	1500	2	563							
DUNKI FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)																			
S-20	1440	1	505	1440	1	505	1440	1 1/2	505	1440	1 1/2	505							
CIRCLING	1460	1	523	1460	1	523	1460	1 1/2	523	1500	2	563							
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. *1640 WHEN USING FORT WAYNE INTL ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FORT WAYNE INTL ALTIMETER SETTING AND INCREASE ALL MDA 140 FEET, INCREASE S-20 CAT C AND D VISIBILITY 1/2 MILE AND CIRCLING CAT C SEE 8260-10																			
CITY AND STATE		ELEVATION: 937 TDZE: 935		AIRPORT NAME:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR OR GPS RWY							
MUNCIE, IN		DELAWARE COUNTY-JOHNSON FIELD		MIE		VOR RWY 20, AMDT 14 08 APR 2010				20									
										AMDT 13									
										DATE		05/10/2007							

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

VISIBILITY 1/2 MILE, CAT D VISIBILITY 1/4 MILE. DUNKI FIX MINIMUMS: INCREASE S-20 CAT C

VISIBILITY 1/4 MILE AND CAT D VISIBILITY 1/2 MILE, INCREASE CIRCLING CAT C AND D VISIBILITY 1/4 MILE.

CHART PROFILE NOTE: MIN ALT 2600 AT MIE VOR/DME.

CHART NOTE: VDP NA WHEN USING FORT WAYNE INTL ALTIMETER SETTING.

CITY AND STATE

MUNCIE, IN

ELEVATION: 937

TDZE: 935

AIRPORT NAME:

DELAWARE COUNTY-JOHNSON FIELD

FACILITY
IDENTIFIER:

MIE

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 20, AMDT 14

08 APR 2010

SUP: VOR OR GPS RWY
20

AMDT: 13

DATED: 05/10/2007