

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Coordinated with:

ATA

☐

ALPA

☐

APA

☐

AOPA

☒

NBAA

☒

OTHER (specify)

☒

ZSE, SEA APCH

TAKEOFF MINIMUMS:

RWY 17: STANDARD.

TAKEOFF OBSTACLES:

RWY 35: TREE 386' 471649/1223417

RWY 35: 400 - 1 OR STANDARD WITH MINIMUM CLIMB OF 210' PER NM
TO 400'.

TEXTUAL DP:

RWY 17: TURN RIGHT, CLIMB VIA HEADING 230 TO INTERCEPT OLM
R-009 THEN DIRECT OLM VORTAC.

DP OBSTACLES:

RWY 35: TURN LEFT, CLIMB VIA HEADING 270 TO INTERCEPT SEA
R-230 THEN DIRECT CARRO INT. CONTINUE CLIMB IN HOLDING (SW,
RT, 047 INBOUND) TO MEA OR ASSIGNED ALTITUDE FOR ROUTE OF
FLIGHT.

City, State

TACOMA, WA

Airport

TACOMA NARROWS

Effective Date

09/06/01

Amdt. No.

3