

U.S. DEPARTMENT of TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

COORDINATED

ATA

☒

AAT

☐

ALPA

☒

APA

☒

AOPA

☒

NBAA

☒

OTHER (specify)

☒

ZLA, ONT ATCT, AMGR, CA AERO

TAKEOFF MINIMUMS:

RWY 8: NA

RWY 26: 1700-2 OR STANDARD WITH A MINIMUM CLIMB OF 300' PER NM TO 4000'.

IFR DEPARTURE PROCEDURE:

CLIMBING LEFT TURN DIRECT PDZ VORTAC. AIRCRAFT DEPARTING PDZ VORTAC R-091 CW R-140 AND R-231 CW R-280 CLIMB ON COURSE. ALL OTHERS CONTINUE IN PDZ VORTAC HOLDING PATTERN (HOLD NE, RT, 210 INBOUND) TO CROSS PDZ VORTAC AT OR ABOVE: R-281 CW R-090, 7700; R-141 CW R-230, 4900.

TAKEOFF OBSTACLES:

DEPARTURE OBSTACLES:

3206 TREES 335900/1171500

CITY AND STATE

REDLANDS, CA

AIRPORT

REDLANDS MUNI

EFFECTIVE

13 AUG 98

AMDT. NO.

ORIG