

PAGE 1 OF 5 PAGES

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: USE RHINELANDER ALTIMETER SETTING, WHEN NOT RECEIVED USE EAGLE RIVER ALTIMETER SETTING AND INCREASE ALL DA 9 FT AND ALL MDA 20 FT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	025/30 CW 205/30 (NOPT)	WOKOG (IF/IAF) (FB)	4400
	205/30 CW 025/30	WOKOG (IF/IAF) (FO)	4400

CITY AND STATE

CRANDON, WI

ELEVATION: 1650

THRE: 1650

AIRPORT NAME:

CRANDON/STEVE CONWAY MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 12, ORIG

8 JANUARY 2015

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	Y55
RUNWAY	RW12
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W12A
LTP/FTP LATITUDE	453132.5725N
LTP/FTP LONGITUDE	0885614.7235W
LTP/FTP ELLIPSOIDAL HEIGHT	+04694
FPAP LATITUDE	453058.5080N
FPAP LONGITUDE	0885417.6315W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1672
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

BBFCFF60

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+05029
FPAP ORTHOMETRIC HEIGHT	+05029

CITY AND STATE

CRANDON, WI

ELEVATION: 1650

THRE: 1650

AIRPORT NAME:

CRANDON/STEVE CONWAY MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 12, ORIG

8 JANUARY 2015

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP Y55 K5FR12	AWOKOG	010WOKOGK5EA0EE	AR	HF		11530050		+ 04400	18000			A JS	
SUSAP Y55 K5FR12	R	010WOKOGK5EA0E	I	IF				+ 04400	18000			A JS	
SUSAP Y55 K5FR12	R	020ZOBEBK5EA1E	F	010TF		11530060		+ 03500				A JS	
SUSAP Y55 K5FR12	R	020ZOBEBK5EA2WALPV			ALNAV/VNAV ALNAV							JS	
SUSAP Y55 K5FR12	R	021HUKASK5EA0E	S	031TF		11540033	V	0244002454		-300		A JS	
SUSAP Y55 K5FR12	R	030RW12 K5PGOGY	M	031TF		11540024		01690		-300		A JS	
SUSAP Y55 K5FR12	R	040		0 M	CA	1154		+ 02050				A JS	
SUSAP Y55 K5FR12	R	050YITUBK5EA0EY		DF				+ 04400				A JS	
SUSAP Y55 K5FR12	R	060YITUBK5EA0EE	R	HM		29570050		+ 04400				A JS	

[illegible][illegible]

QUALITY
9
SERVES

CITY AND STATE CRANDON, WI	ELEVATION: 1650 THRE: 1650	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: CRANDON/STEVE CONWAY MUNI	RNAV	RNAV (GPS) RWY 12, ORIG	AMDT: NONE
			8 JANUARY 2015	DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	WOKOG	WOKOG	010	IAF	HF	R	FO		115.3 (112.3T)	005.0	AA 04400	
		WOKOG	010	FACF	IF		FB				AA 04400	
		ZOBEB	020	FAF	TF		FB	1.0	115.3 (112.3T)	006.0	AA 03500	
		HUKAS	021	SDF	TF		FB	0.3	115.4 (112.4T)	003.3	AA 02440	GS 02454
		RW12	030	MAP	TF		FO	0.3	115.4 (112.4T)	002.4	AT 01690	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		115.4 (112.4T)		AA 02050	
	YITUB	050		DF		FO				AA 04400	
	YITUB	060		HM	R	FO		295.7 (292.7T)	005.0	AA 04400	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HUKAS	N453227.56	W0885924.05	N4532.459	W08859.401
	WOKOG	N453559.42	W0891137.38	N4535.990	W08911.623
	YITUB	N452648.52	W0884003.05	N4526.809	W08840.051
	ZOBEB	N453342.65	W0890343.27	N4533.711	W08903.721
	RW12	N453132.57	W0885614.72	N4531.543	W08856.245

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW12	01650	40

QUALITY
CHECKED

CITY AND STATE CRANDON, WI	ELEVATION: 1650	THRE: 1650	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 8 JANUARY 2015	SUP:
	AIRPORT NAME: CRANDON/STEVE CONWAY MUNI				AMDT: NONE
					DATED: