

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW26							
FJC VORTAC		HANSS (FO)		109.26 / 28.11				3000		CLIMBING RIGHT TURN 3000 DIRECT LIZZI AND HOLD.							
ARD VOR/DME		HANSS (FO)		016.62 / 23.92				3000									
BWZ VOR/DME		CHEWE (FB)		200.39 / 4.00				3000		ADDITIONAL FLIGHT DATA: HOLD NW, RT, 118.05 INBOUND. FAS OBST: 908 AAO 403612N/0745845W SOLOA TO RW26: 3.75/30. CHART CIRCLING ICON							
CHEWE (IAF)		HANSS (NOPT) (FB)		195.01 / 5.00				3000									
SBJ VOR/DME (IAF)		HANSS (NOPT) (FB)		319.71 / 6.26				3000									
HANSS (IF/IAF)		SOLOA (FB)		254.58 / 4.51				2100									
SOLOA (FAF)		RW26 (MAP) (FO)		254.52 / 3.99													
(SEE FORM 8260-10)																	
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)																	
2. HOLD E HANSS, LT, 254.58 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																	
3. FAC: 254.52 FAF: SOLOA DIST FAF TO MAP: 3.99 THLD: 3.99																	
4. MIN. ALT: HANSS 3000, SOLOA 2100																	
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:																	
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:																	
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR																	
8. MSA FROM: RW26 3100																	
MAG VAR: 10W EPOCH YEAR: 1965																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X							
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
CIRCLING	1240	1	760		NA			NA			NA						
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE LEHIGH VALLEY INTL, ALLENTOWN, PA ALTIMETER SETTING. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. (SEE FORM 8260-10)																	
CITY AND STATE PITTS TOWN, NJ		ELEVATION: 480 TDZE: AIRPORT NAME: ALEXANDRIA				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, ORIG 15 OCTOBER 2015						SUP: AMDT: NONE DATED			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW26 (MAP)	880 MSL	254.52	
880 MSL	LIZZI (FO)		3000

NOTES, (CONT.):

CHART PROFILE NOTE: PROCEDURE NA FOR ARRIVALS ON FJC VORTAC AIRWAY RADIAL 053.
CHART PROFILE NOTE: PROCEDURE NA FOR ARRIVALS ON SBJ VOR/DME AIRWAY RADIALS 237 CW 029.
CHART PROFILE NOTE: PROCEDURE NA FOR ARRIVALS ON ARD VOR/DME AIRWAY RADIALS 294 CW 078.

QUALITY
24
CHECKED

CITY AND STATE
PITTSOWN, NJ

ELEVATION: 480 TDZE:
AIRPORT NAME:
ALEXANDRIA

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-B, ORIG
15 OCTOBER 2015

SUP:
AMDT: NONE
DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - N85

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
ARD	010	ARD	IF	FB										V
ARD	020	HANSS	TF	FO	2.0	016.6						AA 03000		EY
ARD	030	HANSS	HF	FO		254.6			L			AA 03000		EE A
BWZ	010	BWZ	IF	FB										V
BWZ	020	CHEWE	TF	FB	2.0	200.4						AA 03000		E A
BWZ	030	HANSS	TF	FB	1.0	195.0						AA 03000		EE B
FJC	010	FJC	IF	FB										V
FJC	020	HANSS	TF	FO	2.0	109.3						AA 03000		EY
FJC	030	HANSS	HF	FO		254.6			L			AA 03000		EE A
SBJ	010	SBJ	IF	FB										V A
SBJ	020	HANSS	TF	FB	1.0	319.7						AA 03000		EE B
	010	HANSS	IF	FB								AA 03000		E I
	020	SOLOA	TF	FB	0.5	254.6				RW26		AA 02100		E F
	030	RW26	TF	FO	0.3	254.5		3.75				AT 00510		GY M
	040		CA	FB		254.5						AA 00880		M
	050	LIZZI	DF	FO					R			AA 03000		EY
	060	LIZZI	HM	FO		118.1			R			AA 03000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
ARD	N401512.03	W0745427.40
BWZ	N404754.36	W0744918.60
FJC	N404336.12	W0752717.12
SBJ	N403458.96	W0744430.46
CHEWE	N404357.93	W0745015.61
HANSS	N403858.88	W0745050.00
LIZZI	N403956.38	W0750855.66
SOLOA	N403702.58	W0745610.78

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW26	N403519.37	W0750054.62	00480	30

CITY AND STATE PITTSOWN, NJ	ELEVATION: 480	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-B, ORIG 15 OCTOBER 2015	SUP:
	AIRPORT NAME: ALEXANDRIA				AMDT: ORIG
					DATED:

QUALITY
4
CHECKED