

ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: 5.43 NM AFTER TIKIY INT/I-FJD 6.66 DME OR AT I-FJD 1.23 DME CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 2000 ON HEADING 080 AND TRV VORTAC R-132 TO ANGEE INT/TRV 22.13 DME AND HOLD. ALTERNATE MA (DO NOT CHART): CLIMB TO 1000 THEN CLIMB TO 2000 ON HEADING 097 AND MLB VOR/DME R-153 TO ANGEE INT/MLB 46.11 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 311.60 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD NW ANGEE INT/MLB 46.11 DME, RT, 152.69 INBOUND. CHART FAS OBST: 117 TREE 272953N/0802411W CHART W-497B. CHART VDP AT 2.19 DME* DISTANCE VDP TO THLD 0.96 NM. *LOC ONLY. CHART IN PLANVIEW AT ZAHZA: TRV VORTAC 12.11 DME. CHART CIRCLING ICON.						
TRV VORTAC		ZAHZA INT/I-FJD 12.68 DME		214.35 / 12.11				2000								
ANGEE INT		FPR NDB		282.40 / 12.06				2000								
FPR NDB		ZAHZA INT/I-FJD 12.68 DME		280.42 / 11.80				2000								
TRV VORTAC		MIMBE (TF) (FB) (RNP 2.00)		238.69 / 7.70				2000								
SHEDS		HASOK (TF) (FB) (RNP 2.00)		353.22 / 6.08				2000								
MIMBE (IAF) (SEE FORM 8260-10)		ZAHZA (TF) (FB) (RNP 1.00)		182.37 / 6.00				2000								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W ZAHZA, RT, 097.47 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 097.47 FAF: TIKIY INT/I-FJD 6.66 DME DIST FAF TO MAP: 5.43 THLD: 5.43 4. MIN. ALT: ZAHZA 2000, TIKIY 1800, SIVYO/I-FJD 3.23 DME 560* 5. DIST TO THLD FROM OM: - MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 949 6. MIN GS INCPT: 1800 GS ALT AT: TIKIY 1800 OM: - MM: - IM: - 7. GS ANGLE: 3.00 TCH: 48.6 8. MSA FROM: FPR NDB 2600										MAG VAR: 7W		EPOCH YEAR: 2015				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		<input checked="" type="checkbox"/>						
CATEGORY ==>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
S-ILS 10R	273	3/4	250	273	3/4	250	273	3/4	250	273	3/4	250				
S-LOC 10R	560	1	537	560	1	537	560	1 1/2	537	560	1 1/2	537				
CIRCLING	560	1	537	560	1	537	880	2 1/2	857	880	2 3/4	857				
SIVYO FIX MINIMUMS (DME REQUIRED)																
S-LOC 10R	380	1	357	380	1	357	380	1	357	380	1	357				
CIRCLING	460	1	437	480	1	457	880	2 1/2	857	880	2 3/4	857				
NOTES: CHART NOTE: AUTOPILOT COUPLED APPROACH NA BELOW 720 MSL. CHART SPEED ICON IN PLANVIEW AT MIMBE : MAX 210 KIAS. CHART SPEED ICON IN PLANVIEW AT HASOK : MAX 210 KIAS. CHART PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT. (CONTINUED ON PAGE 2)																
CITY AND STATE FORT PIERCE, FL		ELEVATION: 23 TDZE: 23 AIRPORT NAME: TREASURE COAST INTL				FACILITY IDENTIFIER: I-FJD		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 10R, AMDT 4C 2 MARCH 2017				SUP: AMDT: 4B DATED 06/23/2016				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HASOK (IAF)	ZAHZA (NOPT) (TF) (FB) (RNP 1.00)	017.36 / 6.00	2000
ZAHZA INT/I-FJD 12.68 DME (IF/IAF)	TIKIY INT/I-FJD 6.66 DME	097.47 / 6.02 (I-FJD)	1800

NOTES, (CONT.):

CHART NOTE: VDP NA WITH VERO BEACH ALTIMETER SETTING.

WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VERO BEACH ALTIMETER SETTING AND INCREASE ALL DA 23 FEET AND ALL MDA 40 FEET; INCREASE S-ILS ALL CATS, S-LOC CAT C/D, AND SIVYO FIX MINIMUMS S-LOC CAT C/D VISIBILITY 1/8 MILE; AND INCREASE CIRCLING AND SIVYO FIX MINIMUMS CIRCLING CAT C/D VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: MIMBE (IAF): GPS REQUIRED.

CHART PLANVIEW NOTE: HASOK (IAF): GPS REQUIRED.

CITY AND STATE

FORT PIERCE, FL

ELEVATION: 23

TDZE: 23

AIRPORT NAME:

TREASURE COAST INTL

 FACILITY
IDENTIFIER:

I-FJD

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

ILS OR LOC RWY 10R, AMDT 4C

2 MARCH 2017

SUP:

AMDT:

DATED: 06/23/2016

 QUALITY
18
CHECKED