

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet; MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE									
AGUDE	JANIL (FO)	000.06 / 20.44	3000	LP: RW18 LNAV: RW18								
ALEEN (IAF)	JANIL (NOPT) (FB)	207.44 / 13.77	3000	CLIMB TO 3000 DIRECT FISOM AND HOLD.								
JANIL (IF/IAF)	EBAYI (FB)	177.36 / 6.03	2700									
EBAYI (FAF)	UHVAG/1.80 NM TO RW18 (FB)	177.38 / 3.17		ADDITIONAL FLIGHT DATA: HOLD S, RT, 357.37 INBOUND. CHART FAS OBST: 1194 TREE 451751N/0922244W CHART FAS OBST: 1219 WATER TWR 451752N/0922150W WAAS CHANNEL # 77732 REFERENCE PATH ID: W18A CHART CIRCLING ICON LTP HAE: 299.1 M								
UHVAG/1.80 NM TO RW18	RW18 (MAP) (FO)	177.38 / 1.80										
RW18 (MAP)	1488 MSL	177.38										
1488 MSL	FISOM (FO)		3000									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N JANIL, RT, 177.36 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>177.38</u> FAF: <u>EBAYI</u> DIST FAF TO MAP: <u>4.97</u> THLD: <u>4.97</u> 4. MIN. ALT: JANIL 3000, EBAYI 2700, UHVAG/1.80 NM TO RW18 1680 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u>150</u> HAT: <u>100</u> HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: RW18 3200				MAG VAR: 1E EPOCH YEAR: 2005								
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X								
CATEGORY ==>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1500	1	422	1500	1	422	1500	1 1/4	422		NA	
LNAV MDA	1600	1	522	1600	1	522	1600	1 1/2	522		NA	
CIRCLING	1740	1	652	1740	1	652	1740	1 3/4	652		NA	
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ALEEN ON V148 NORTHEAST BOUND AND V55 NORTHWEST BOUND. (SEE FORM 8260-10)												
CITY AND STATE		ELEVATION: 1088 THRE: 1078		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:				
AMERY, WI		AIRPORT NAME: AMERY MUNI				RNAV (GPS) RWY 18, AMDT 1 19 SEPTEMBER 2013		AMDT: ORIG				
								DATED 03/17/2005				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: USE NEW RICHMOND ALTIMETER SETTING; WHEN NOT RECEIVED, USE OSCEOLA ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET AND LP/LNAV CAT C VISIBILITY 1/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PROFILE NOTE: DESCENT ANGLE NA.

QUALITY
A
CHECKED

CITY AND STATE AMERY, WI	ELEVATION: 1088	THRE: 1078	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 19 SEPTEMBER 2013	SUP:
	AIRPORT NAME:				AMDT: ORIG
	AMERY MUNI				DATED: 03/17/2005

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAHH
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	451711.8725N
LTP/FTP LONGITUDE	0922232.2025W
LTP/FTP ELLIPSOIDAL HEIGHT	+02991
FPAP LATITUDE	451542.8200N
FPAP LONGITUDE	0922228.6300W
THRESHOLD CROSSING HEIGHT (TCH)	00000.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	00.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

6C1E8233

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+03285
FPAP ORTHOMETRIC HEIGHT	+03285

QUALITY
4
CHECKED

CITY AND STATE:

AMERY, WI

ELEVATION: 1088

THRE: 1078

AIRPORT NAME:

AMERY MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, AMDT 1

19 SEPTEMBER 2013

SUP:

AMDT: ORIG

DATED: 03/17/2005

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KAHHK5FR18	AAGUDE	010AGUDEK5EA0E	IF						18000		A JS	
SUSAP	KAHHK5FR18	AAGUDE	020JANILK5EA0EY	020TF			00010204	+	03000			A JS	
SUSAP	KAHHK5FR18	AAGUDE	030JANILK5EA0EE	AR HF			17740040	+	03000			A JS	
SUSAP	KAHHK5FR18	AALEEN	010ALEENK5EA0E	A IF						18000		A JS	
SUSAP	KAHHK5FR18	AALEEN	020JANILK5EA0EE	B 010TF			20740138	+	03000			A JS	
SUSAP	KAHHK5FR18	R	010JANILK5EA0E	I IF				+	03000	18000		A JS	
SUSAP	KAHHK5FR18	R	020EBAYIK5EA1E	F 051TF			17740060	+	02700		RW18	K5PGA	JS
SUSAP	KAHHK5FR18	R	020EBAYIK5EA2WALP		N	ALNAV							JS
SUSAP	KAHHK5FR18	R	021UHVAGK5EA0E	S 031TF			17740032	+	01680			A JS	
SUSAP	KAHHK5FR18	R	030RW18 K5PG0GY	M 031TF			17740018		01600	000		A JS	
SUSAP	KAHHK5FR18	R	040	0 M CA			1774	+	01488			A JS	
SUSAP	KAHHK5FR18	R	050FISOMK5EA0EY	DF				+	03000			A JS	
SUSAP	KAHHK5FR18	R	060FISOMK5EA0EE	R HM			35740040	+	03000			A JS	

[illegible][illegible]

1	2	3	4	5	6	7	8	9	0	1	2	3	4
---	---	---	---	---	---	---	---	---	---	---	---	---	---

CITY AND STATE AMERY, WI	ELEVATION: 1088	THRE: 1078	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 18, AMDT 1	AMDT: ORIG
	AMERY MUNI		RNAV	19 SEPTEMBER 2013	DATED: 03/17/2005

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

MSA 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KAHK5SRW18 K5PG 0 18018003225 M

QUALITY
A
CHECKED

CITY AND STATE AMERY, WI	ELEVATION: 1088	THRE: 1078	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 19 SEPTEMBER 2013	SUP:
	AIRPORT NAME: AMERY MUNI	AMDT: ORIG			
	DATED: 03/17/2005				

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	AGUDE	AGUDE	010		IF		FB					
	AGUDE	JANIL	020		TF		FO	2.0	000.1 (001.1T)	020.4	AA 03000	
	AGUDE	JANIL	030	IAF	HF	R	FO		177.4 (178.4T)	004.0	AA 03000	
	ALEEN	ALEEN	010	IAF	IF		FB					
	ALEEN	JANIL	020		TF		FB	1.0	207.4 (208.4T)	013.8	AA 03000	
		JANIL	010	FACF	IF		FB				AA 03000	
		EBAYI	020	FAF	TF		FB	0.5	177.4 (178.4T)	006.0	AA 02700	
		UHVAG	021	SDF	TF		FB	0.3	177.4 (178.4T)	003.2	AA 01680	
		RW18	030	MAP	TF		FO	0.3	177.4 (178.4T)	001.8	AT 01600	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		177.4 (178.4T)		AA 01488	
	FISOM	050		DF		FO				AA 03000	
	FISOM	060		HM	R	FO		357.4 (358.4T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	AGUDE	N450745.68	W0922330.99	N4507.761	W09223.517
	ALEEN	N454018.41	W0921339.69	N4540.307	W09213.662
	EBAYI	N452209.78	W0922244.15	N4522.163	W09222.736
	FISOM	N450532.75	W0922204.12	N4505.546	W09222.069
	JANIL	N452811.50	W0922258.88	N4528.192	W09222.981
	UHVAG	N451859.81	W0922236.53	N4518.997	W09222.609
	RW18	N451711.87	W0922232.20	N4517.198	W09222.537

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18	01078	00

QUALITY
CHECKED

CITY AND STATE AMERY, WI	ELEVATION: 1088 THRE: 1078	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 19 SEPTEMBER 2013	SUP:
	AIRPORT NAME: AMERY MUNI			AMDT: ORIG
				DATED: 03/17/2005