

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
				MAP: MZZ VOR/DME	
				CLIMB TO 2500 THEN LEFT TURN DIRECT MZZ VOR/DME AND HOLD.	
				ADDITIONAL FLIGHT DATA: HOLD SW, LT, 067.00 INBOUND. FAS OBST: 949 TREE 402901N/0854133W FAC CROSSES RWY C/L EXTENDED 188 FROM THLD.	

1. PT R SIDE OF COURSE 214.00 OUTBOUND 2400 FT WITHIN 10 MILES OF MZZ VOR/DME (IAF)

2.

3. FAC 034.00 FAF _____ DIST FAF TO MAP _____ THLD _____

4. MIN. ALT _____

8. MSA FROM: MZZ VOR/DME 2900

MAG VAR: 3W

EPOCH YEAR: 85

MINIMUMS

TAKEOFF:	<input type="checkbox"/>	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	<input checked="" type="checkbox"/>				
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-4	1260	1/2	401	1260	1/2	401	1260	3/4	401	1260	1	401			
CIRCLING	1280	1	421	1320	1	461	1320	1 1/2	461	1420	2	561			

NOTES: CHART NOTES:

IF LOCAL ALTIMETER SETTING NOT RECEIVED USE FORT WAYNE INTL ALTIMETER SETTING AND INCREASE ALL MDA'S 100 FEET.

FOR INOPERATIVE MALSR, INCREASE CAT D VISIBILITY TO 1 1/4

CITY AND STATE MARION, IN	ELEVATION: 859 TDZE: 859	FACILITY IDENTIFIER: MZZ	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: SEP 30 2004 VOR RWY 4, AMDT 13	SUP
	AIRPORT NAME: MARION MUNI			AMDT 12
	DATE 22 JUN 95			