

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/30/13	IN	Marion	Marion Muni	3/9057	4/4/13	RNAV (GPS) RWY 4, Orig

FDC **3/9057** MZZ FI/P IAP MARION MUNI, MARION, IN. RNAV (GPS) RWY 4, ORIG... LNAV/VNAV DA 1259/HAT 400, VIS 1 ALL CATS LNAV MDA 1280/HAT 421. VDP AT 1.16 NM TO RW04, LNAV ONLY. 34:1 IS CLEAR. CIRCLING CAT A MDA 1300/HAA 441, VIS CAT A/B 1. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FORT WAYNE INTL ALTIMETER SETTING AND INCREASE ALL DA 91 FEET AND ALL MDA 100 FEET, INCREASE LPV ALL CATS VISIBILITY 1/2 MILE, LNAV/VNAV ALL CATS VISIBILITY AND LNAV CAT C/D VISIBILITY 1/4 MILE. DELETE NOTES: WHEN VGSI INOP, CIRCLING RWY 15, 33 NA AT NIGHT. FOR INOPERATIVE MALSR, INCREASE LNAV CAT A/B/C VISIBILITIES TO 1 AND CAT D TO 1 1/4. CHART NOTE: CIRCLING TO RWY 15/33 NA AT NIGHT. CHART NOTE: FOR INOPERATIVE MALSR WHEN USING FORT WAYNE INTL ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 1/4, LNAV/VNAV ALL CATS VISIBILITY TO 1 3/4, AND LNAV CAT A/B VISIBILITY TO 1. FOR INOPERATIVE MALSR, INCREASE LNAV CAT A/B VISIBILITY TO 1 AND CAT B TO 1 1/4. CHANGE BARO VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). THIS IS RNAV (GPS) RWY 4, ORIG-A.