

**RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE,
TITLE 14 CFR PART 97.33**

CLIMB TO 2500 DIRECT CANBO AND ON TRACK 073.36 TO MOSME
AND ON TRACK 024.98 TO TEB VOR/DME AND HOLD. WHEN
AUTHORIZED BY ATC. CONTINUE CLIMB-IN-HOLD TO 3000.

MISSED APPROACH

ADDITIONAL FLIGHT DATA:
HOLD NW, RT, 157.00 INBOUND.
DISTANCE TO THLD FROM 369 HAT: 0.99 NM.
CHART MANDATORY 2800 AT ISACE.
ROUTE TYPE: A, H
ROUTE TYPE QUALIFIER 1: F
ROUTE TYPE QUALIFIER 2: S
CHART MAXIMUM ALTITUDE IN PLANVIEW AT KILMA 4000
#TCH 66.1 MSL (DO NOT CHART)

- MAG VAR: 13W EPOCH YEAR: 1985

[illegible][illegible]

AMDT:	ORIG-C
DATED	11/15/2012

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

VISIBILITY TO 1 3/4 ALL CATS.

CHART NOTE: *MISSED APPROACH REQUIRES MINIMUM CLIMB OF 317 FEET PER NM TO 700.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT KILMA ON V433 WESTBOUND.

CITY AND STATE
NEWARK, NJ

ELEVATION: 18 TDZE: 11
AIRPORT NAME:
NEWARK LIBERTY INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (RNP) Z RWY 4R, ORIG-D
18 SEPTEMBER 2014

SUP:
AMDT: ORIG-C
DATED: 11/15/2012

RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (RNP)

[illegible]

CITY AND STATE
NEWARK, NJ

ELEVATION: 18 TDZE: 1
AIRPORT NAME:
NEWARK LIBERTY INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (RNP) Z RWY 4R, ORIG-D
 18 SEPTEMBER 2014

SUP:	
AMDT:	ORIG-C
DATED:	11/15/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

MSA 1234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KEWRK6SRW04RK6PG 0 18018003025 M

CITY AND STATE NEWARK, NJ	ELEVATION: 18	TDZE: 11	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (RNP) Z RWY 4R, ORIG-D 18 SEPTEMBER 2014	SUP:
	AIRPORT NAME: NEWARK LIBERTY INTL	AMDT: ORIG-C			
	DATED: 11/15/2012				

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (RNP)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	KILMA	KILMA	010	IAF	IF		FB				AB 04000	
	KILMA	ISACE	020		TF		FB	1.0			AT 02800	
		ISACE	010	FACF	IF		FB				AT 02800	
		COWWE	020	FAF	TF		FB	0.5			AA 01700	
		RW04R	030	MAP	TF		FO	0.3			AT 00066	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		038.8 (025.8T)		AA 00380	
	CANBO	050		DF		FB					
	MOSME	060		TF		FB	1.0				
	TEB	070		TF		FO	1.0			AA 02500	
	TEB	080		HM	R	FO		157.0 (144.0T)	004.0	AA 02500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	TEB	N405055.39	W0740344.07	N4050.923	W07403.735
	KILMA	N402909.70	W0742408.82	N4029.162	W07424.147
	CANBO	N404304.98	W0740854.64	N4043.083	W07408.911
	COWWE	N403616.66	W0741313.99	N4036.278	W07413.233
	ISACE	N403052.16	W0741639.42	N4030.869	W07416.657
	MOSME	N404433.08	W0740530.94	N4044.551	W07405.516
	RW04R	N404049.89	W0741020.55	N4040.832	W07410.343

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04R	00011	55

CITY AND STATE NEWARK, NJ	ELEVATION: 18	TDZE: 11	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (RNP) Z RWY 4R, ORIG-D 18 SEPTEMBER 2014	SUP:
	AIRPORT NAME: NEWARK LIBERTY INTL				AMDT: ORIG-C
					DATED: 11/15/2012