

**Federal Aviation
Administration**

Transmittal Letter 16-13

May 6, 2016

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
23-Jun-16	MS	Hattiesburg	Hattiesburg Bobby L Chain Muni	6/4767	04/18/16	RNAV (GPS) Z RWY 13, Amdt 1

AIRAC Date: 23 JUNE 2016

FDC 6/4767 HBG IAP HATTIESBURG BOBBY L CHAIN MUNI, HATTIESBURG, MS. RNAV (GPS) Z RWY 13, AMDT 1...
CHANGE THRE 149 TO TDZE 151. CIRCLING CATS B/C MDA 700/HAA 549.. LPV DA 351. LNAV/VNAV DA 458.
LNAV HAT 429 ALL CATS. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE
3.00/TCH 50). CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED,
USE HATTISBURG LAUREL RGNL ALTIMETER SETTING AND INCREASE ALL DA 51 FEET AND INCREASE ALL MDA 60
FEET. INCREASE LPV ALL CATS AND LNAV CAT C/D VISIBILITY 1/8 MILE, LNAV/VNAV ALL CATS AND CIRCLING CAT
C VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) Z RWY 13, AMDT 1A. 1602161925-PERM