

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.91 MILES AFTER DNV VORTAC OR AT DNV 4.91 DME FIX CLIMBING RIGHT TURN TO 2400 DIRECT DNV VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 812 TREE 401244N/0873609W CHART VDP AT 4.22 DME; DISTANCE VDP TO THLD 1.12 MILES. DNV VORTAC TO RW21: 2.92/46. FAC CROSSES RWY C/L EXTENDED 2673 FROM THLD.							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N DNV VORTAC, RT, 192.79 INBOUND, 2400 FT. IN LIEU OF PT (IAF) 3. FAC 192.79 FAF DNV VORTAC _____ DIST FAF TO MAP 4.91 THLD 5.34 4. MIN. ALT DNV VORTAC 2400 8. MSA FROM: DNV VORTAC 270-180 2400, 180-270 3000										MAG VAR: 2E		EPOCH YEAR: 1965					
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @					
CATEGORY >>>>>>		A		B		C		D		E							
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-21		1100	3/4	403	1100	3/4	403	1100	3/4	403	1100	1	403				
CIRCLING		1120	1	423	1160	1	463	1160	1 1/2	463	1260	2	563				
NOTES: CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-21 CATS A AND B VISIBILITY TO 1, AND CAT D VISIBILITY TO 1 1/4. CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE UNIVERSITY OF ILLINOIS-WILLARD ALTIMETER SETTING AND INCREASE ALL MDAS 100 FT. SEE 8260-10																	
CITY AND STATE		ELEVATION: 697		TDZE: 697		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO.:		SUP VOR OR GPS RWY							
DANVILLE, IL						DNV		VOR RWY 21, AMDT 14		21							
								AUG 30 2007		AMDT		13A					
										DATE		07/13/1998					



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT DNV VORTAC ON V171 SOUTHBOUND AND V251 SOUTHWEST BOUND.

CHART NOTE: VDP NA WHEN USING UNIVERSITY OF ILLINOIS-WILLARD ALTIMETER SETTING.

CITY AND STATE

DANVILLE, IL

ELEVATION: 697

TDZE: 697

AIRPORT NAME:

VERMILION COUNTY

FACILITY
IDENTIFIER:

DNV

PROCEDURE NO./AMDT NO.:

VOR RWY 21, AMDT 14

AUG 30 2007

SUP: VOR OR GPS RWY
21

AMDT: 13A

DATED: 07/13/1998