

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 12, 17, 27, 30, 35 STANDARD.

RWY 9, 200-1 1/4 OR STANDARD WITH MINIMUM CLIMB OF 207 FT PER NM TO 300, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1,300 FT PRIOR TO DEPARTURE END OF RUNWAY.

(2) TEXTUAL DEPARTURE PROCEDURE:

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 9, TREES BEGINNING 558' FROM DER, 39' RIGHT OF CENTERLINE, UP TO 100' AGL/105' MSL. TREES BEGINNING 625' FROM DER, 7' LEFT OF CENTERLINE, UP TO 100' AGL/137' MSL. TOWER 1.1 NM FROM DER, 1,398' RIGHT OF CENTERLINE, 164' AGL/199' MSL.

NOTE: RWY 12, TREES BEGINNING AT DER, 285' RIGHT OF CENTERLINE, UP TO 100' AGL/131' MSL. TREES BEGINNING 1,337' FROM DER, 211' LEFT OF CENTERLINE, UP TO 64' AGL/93' MSL.

NOTE: RWY 17, TREES BEGINNING 237' FROM DER, 110' RIGHT OF CENTERLINE, UP TO 100' AGL/164' MSL. TREES BEGINNING 796' FROM DER, 478' LEFT OF CENTERLINE, UP TO 100' AGL/169' MSL.
(CONTINUED ON PAGE 2)

(4) CONTROLLING OBSTACLES:

RWY 9: 199 MSL TOWER 293920.10N/0813938.20W

QUALITY
9
CHECKED

(5) City, State

PALATKA, FL

(6) Airport

PALATKA MUNI-LT KAY LARKIN FIELD

(7) Effective Date

22 OCT 2009

(8) Amdt. No.

ORIG