

RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES											MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE				ALTITUDE		RNP: DA					
LARII (IAF)		JAAJJ (TF) (FB) (RNP 1.00)			094.74 / 7.39				5000		CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 3500 DIRECT TROYS AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 185.00 INBOUND. DISTANCE TO THLD FROM 352 HAT: 0.95 NM. CHART MINIMUM 6000 AT BBRAD. #TCH 1064.5 MSL (DO NOT CHART) ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 2: S CODE APPROACH TRANSITION AT JAAJJ. CHART MINIMUM 7000 AT REAKS. ROUTE TYPE QUALIFIER 1: F CODE FACF AT BAZAR. CHART MINIMUM 5000 AT LARII.					
BBRAD (IAF)		KRSON (TF) (FB) (RNP 1.00)			166.77 / 4.54				5000							
KRSON		JAAJJ (RF) (FB) (RNP 1.00)			(2.50 NM RADIUS CCW (CFZHW))/3.14				5000							
JAAJJ		BAZAR (TF) (FB) (RNP 1.00)			094.82 / 3.45				4000							
REAKS (IAF)		EEERR (TF) (FB) (RNP 1.00)			274.87 / 3.86				6000							
(SEE FORM 8260-10)																
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)																
2. PROFILE STARTS AT BAZAR																
3. FAC: <u>094.91</u> FAF: <u> </u> DIST FAF TO MAP: <u> </u> THLD: <u> </u>																
4. MIN. ALT: BAZAR 4000, SCHEL 2900																
5. DIST TO THLD FROM OM: <u>5.76</u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>																
6. MIN GS INCPT: <u>2900</u> GS ALT AT: SCHEL 2900 OM: <u> </u> MM: <u> </u> IM: <u> </u>																
7. GS ANGLE: <u>3.00</u> TCH: <u>49.9</u> 34:1 IS NOT CLEAR																
8. MSA FROM: RW08L 3200																
MINIMUMS																
TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>											ALTERNATE: N A		STANDARD			
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
AUTHORIZATION REQUIRED																
RNP 0.15 DA	1367	4000	352	1367	4000	352	1367	4000	352	1367	4000	352				
RNP 0.30 DA	1435	4700	420	1435	4700	420	1435	4700	420	1435	4700	420				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -7C (20F) OR ABOVE 54C (130F). CHART NOTE: GPS REQUIRED. CHART PLANVIEW NOTE AT LARII : MAX 210 KIAS. CHART PLANVIEW NOTE AT BBRAD : MAX 210 KIAS. (SEE FORM 8260-10)																
CITY AND STATE				ELEVATION: 1026 TDZE: 1015				FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
ATLANTA, GA				AIRPORT NAME:				RNAV		RNAV (RNP) Z RWY 8L, ORIG				AMDT: NONE		
				HARTSFIELD - JACKSON ATLANTA INTL						18 SEPTEMBER 2014				DATED		

QUALITY
4
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33				
TERMINAL ROUTES, (CONT.):				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
EEERR	BAZAR (RF) (FB) (RNP 1.00)	(2.50 NM RADIUS CCW (CFZHV))/7.85	4000	
BAZAR (IF)	SCHEL (TF) (FB) (RNP 1.00)	094.86 / 4.37	2900	
SCHEL	RW08L (MAP) (TF) (FO)	094.91 / 5.76		
RW08L (MAP)	1500 MSL (CA)	094.91	1500	
1500 MSL	TROYS (DF) (FO)		3500	
NOTES, (CONT.):				
CHART PLANVIEW NOTE AT REAKS : MAX 210 KIAS.				
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.				
CHART NOTE: FOR INOPERATIVE ALSF, INCREASE RNP 0.15 DA ALL CATS VISIBILITY TO RVR 5800 AND RNP 0.30 VISIBILITY ALL CATS TO 1 3/8 MILES.				
CHART PLANVIEW NOTE AT BBRAD: RADAR REQUIRED.				
CHART PLANVIEW NOTE ADJACENT TO BBRAD: RF REQUIRED.				
CHART PLANVIEW NOTE ADJACENT TO REAKS: RF REQUIRED.				
CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 9L OR 9R OR 10, OR RWYS 9L AND 10 - ARRIVALS FROM BBRAD AND REAKS NA DURING SIMULTANEOUS TRIPLE APPROACHES.				
CITY AND STATE	ELEVATION: 1026	TDZE: 1015	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
ATLANTA, GA	AIRPORT NAME:		RNAV	RNAV (RNP) Z RWY 8L, ORIG
	HARTSFIELD - JACKSON ATLANTA INTL			18 SEPTEMBER 2014
			SUP:	
			AMDT:	NONE
			DATED:	

QUALITY
4
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KATLK7FH08LZ	ABBRAD	010BBRADK7PC0E	A	IF				+	06000	18000210		A-FS
SUSAP	KATLK7FH08LZ	ABBRAD	020KRSONK7PC0E		010TF				+	05000			A FS
SUSAP	KATLK7FH08LZ	ABBRAD	030JAAJJK7PC0E	L010RF		0025001668	09480031		+	05000		CFZHW K7PCA	FS
SUSAP	KATLK7FH08LZ	ABBRAD	040BAZARK7PC0EE	B	010TF				+	04000			A FS
SUSAP	KATLK7FH08LZ	ALARII	010LARI IK7PC0E	A	IF				+	05000	18000210		A-FS
SUSAP	KATLK7FH08LZ	ALARII	020JAAJJK7PC0E		010TF				+	05000			A FS
SUSAP	KATLK7FH08LZ	ALARII	030BAZARK7PC0EE	B	010TF				+	04000			A FS
SUSAP	KATLK7FH08LZ	AREAKS	010REAKSK7PC0E	A	IF				+	07000	18000210		A-FS
SUSAP	KATLK7FH08LZ	AREAKS	020EEERRK7PC0E		010TF				+	06000			A FS
SUSAP	KATLK7FH08LZ	AREAKS	030BAZARK7PC0EE	BL010RF		0025002749	09490079		+	04000		CFZHV K7PCA	FS
SUSAP	KATLK7FH08LZ	H	010BAZARK7PC0E	I	IF				+	04000	18000		A FS
SUSAP	KATLK7FH08LZ	H	020SCHELK7PC1E	F	010TF				+	02900		RW08L K7PGA	FS
SUSAP	KATLK7FH08LZ	H	020SCHELK7PC2W							A031A152			FS
SUSAP	KATLK7FH08LZ	H	030RW08LK7PG0GY	M	031TF					01065	-300		A FS
SUSAP	KATLK7FH08LZ	H	040		0 M		0949		+	01500			A FS
SUSAP	KATLK7FH08LZ	H	050TROYSK7PC0EY		DF				+	03500			A FS
SUSAP	KATLK7FH08LZ	H	060TROYSK7PC0EE	R	HM		18500040		+	03500			A FS

QUALITY
15
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated) Page 3 of 5 Pages

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KATLK7GRW08L 0090000950 N33385832W084262049-0300 +0279801015000050150IIHFW3

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1	2	3	4	5	6	7	8	9	0	1	2	3

SUSAP KATLK7SRW08LK7PG				0	18018003125							M	

QUALITY
15
CHECKED

CITY AND STATE
ATLANTA, GA

ELEVATION: 1026 TDZE: 1015
AIRPORT NAME:
HARTSFIELD - JACKSON ATLANTA INTL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (RNP) Z RWY 8L, ORIG
18 SEPTEMBER 2014

SUP:
AMDT: NONE
DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (RNP)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	BBRAD	BBRAD	010	IAF	IF		FB				AA 06000	AB 210
	BBRAD	KRSON	020		TF		FB	1.0			AA 05000	
	BBRAD	JAAJJ	030		RF	L	FB	1.0		003.1	AA 05000	
	BBRAD	BAZAR	040		TF		FB	1.0			AA 04000	
	LARII	LARII	010	IAF	IF		FB				AA 05000	AB 210
	LARII	JAAJJ	020		TF		FB	1.0			AA 05000	
	LARII	BAZAR	030		TF		FB	1.0			AA 04000	
	REAKS	REAKS	010	IAF	IF		FB				AA 07000	AB 210
	REAKS	EEERR	020		TF		FB	1.0			AA 06000	
	REAKS	BAZAR	030		RF	L	FB	1.0		007.9	AA 04000	
		BAZAR	010	FACF	IF		FB				AA 04000	
		SCHEL	020	FAF	TF		FB	1.0			AA 02900	
		RW08L	030	MAP	TF		FO	0.3			AT 01065	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		094.9 (089.9T)		AA 01500	
		TROYS	050		DF		FO				AA 03500	
		TROYS	060		HM	R	FO		185.0 (180.0T)	004.0	AA 03500	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		BAZAR	N333857.41		W0843828.63		N3338.957		W08438.477			
		BBRAD	N334459.48		W0844710.04		N3344.991		W08447.167			
		CFZHV	N334127.69		W0843829.08		N3341.462		W08438.485			
		CFZHW	N334127.09		W0844237.10		N3341.452		W08442.618			
		EEERR	N334357.96		W0843829.63		N3343.966		W08438.494			
		JAAJJ	N333856.82		W0844236.53		N3338.947		W08442.609			
		KRSON	N334040.15		W0844527.86		N3340.669		W08445.464			
		LARII	N333855.11		W0845127.67		N3338.919		W08451.461			
		REAKS	N334358.59		W0843352.12		N3343.977		W08433.869			
		SCHEL	N333857.95		W0843314.74		N3338.966		W08433.246			
		TROYS	N335246.30		W0842606.26		N3352.772		W08426.104			
		RW08L	N333858.32		W0842620.49		N3338.972		W08426.342			
RUNWAY DATA		RWY	THRESHOLD ELEVATION		TCH							
		RW08L	01015		50							
CITY AND STATE		ELEVATION: 1026		TDZE: 1015		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:			SUP:	
ATLANTA, GA		AIRPORT NAME:		HARTSFIELD - JACKSON ATLANTA INTL		RNAV		RNAV (RNP) Z RWY 8L, ORIG			AMDT: NONE	
								18 SEPTEMBER 2014			DATED:	

