

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: PCW NDB							
										CLIMBING RIGHT TURN TO 2500 IN PCW NDB HOLDING PATTERN.							
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 275.76 INBOUND. CHART FAS OBST: 719 TREE 413211N/0825142W 784 AAO 413037N/0824718W CHART RESTRICTED AREAS 5502 A & B. AYSEL TO RW27: 2.70/40. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 2493 FROM THLD.							
1. PT <u> L </u> SIDE OF COURSE <u> 095.76 </u> OUTBOUND <u> 2300 </u> FT WITHIN <u> 10 </u> MILES OF <u> PCW NDB </u> (IAF) 2. _____ 3. FAC <u> 275.76 </u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u> AYSEL/DJB 30.47 DME 1400* </u> 8. MSA FROM: <u> PCW NDB 360-270 2500, 270-360 3100 </u>														MAG VAR: 7W		EPOCH YEAR: 2010	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A <input checked="" type="checkbox"/> X							
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-27	1400	1	812	1400	1 1/4	812	1400	2 1/2	812	1400	2 1/2	812					
CIRCLING	1400	1	810	1400	1 1/4	810	1400	2 1/2	810	1580	3	990					
AYSEL FIX MINIMUMS (DME REQUIRED)																	
S-27	1060	1	472	1060	1	472	1060	1 3/8	472	1060	1 3/8	472					
CIRCLING	1140	1	550	1140	1	550	1180	1 1/2	590	1580	3	990					
NOTES: CHART PLANVIEW NOTE: RADAR REQUIRED. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TOLEDO EXECUTIVE ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND ALL VISIBILITIES 1/4 MILE. (SEE FORM 8260-10)																	
CITY AND STATE PORT CLINTON, OH				ELEVATION: 590 AIRPORT NAME: CARL R KELLER FIELD		TDZE: 588		FACILITY IDENTIFIER: PCW		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 27, AMDT 14 5 MARCH 2015				SUP AMDT 13A DATE 08/27/2009			

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART NOTE: NIGHT LANDING: RWY 9, 18, 36 NA. NIGHT LANDING: RWY 27 NA FOR CAT C/D AIRCRAFT.****CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.*****1480 WHEN USING TOLEDO EXECUTIVE ALTIMETER SETTING.**

CITY AND STATE

PORT CLINTON, OH

ELEVATION: 590

TDZE: 588

AIRPORT NAME:

CARL R KELLER FIELD

FACILITY
IDENTIFIER:

PCW

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 27, AMDT 14

5 MARCH 2015

SUP:

AMDT: 13A

DATED: 08/27/2009

