

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>								<b>MISSED APPROACH</b>							
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18R  CLIMB TO 1100 THEN CLIMBING RIGHT TURN TO 3000 DIRECT LIKES AND HOLD.  <b>ADDITIONAL FLIGHT DATA:</b> HOLD NE, RT, 223.97 INBOUND. CHART FAS OBST: 958 TOWER 325903N/0970355W DISTANCE TO THLD FROM 200 HAT: 0.44 NM. CHART VDP AT 1.68 MILES TO RW18R* *LNAV ONLY. WAAS CHANNEL # 99407 REFERENCE PATH ID: W18B LTP HAE: 157.7 M											
ICKEL (IF)	YOHAN (FB)	176.25 / 3.15	3000												
YOHAN	LEGRE (FB)	176.25 / 6.29	3000												
LEGRE	NETEE (FB)	176.25 / 2.05	2400												
NETEE (FAF)	RW18R (MAP) (FO)	176.25 / 5.45													
RW18R (MAP)	1100 MSL	176.25	1100												
1100 MSL	LIKES (FO)		3000												
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. PROFILE STARTS AT ICKEL 3. FAC: <u>176.25</u> FAF: <u>NETEE</u> DIST FAF TO MAP: <u>5.45</u> THLD: <u>5.45</u> 4. MIN. ALT: ICKEL 4000, YOHAN 3000, LEGRE 3000, NETEE 2400 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>2400</u> GS ALT AT: <u>NETEE 2400</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>58.6</u> 34:1 IS CLEAR 8. MSA FROM: <u>RW18R 3600</u>				MAG VAR: 4E EPOCH YEAR: 2015											
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	807	2400	200	807	2400	200	807	2400	200	807	2400	200			
LNAV/VNAV DA	980	4000	373	980	4000	373	980	4000	373	980	4000	373			
LNAV MDA	1220	2400	613	1220	2400	613	1220	1 3/8	613	1220	1 3/8	613			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -4C (25F) OR ABOVE 54C (130F). CHART NOTE: FOR INOPERATIVE ALSF, INCREASE LNAV CAT C/D VISIBILITY TO 1 3/4 MILE. CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 17L/C/R. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 607 TDZE: 607		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
DALLAS-FORT WORTH, TX		AIRPORT NAME:		DALLAS/FORT WORTH INTL		RNAV (GPS) RWY 18R, AMDT 1A 18 SEPTEMBER 2014				AMDT: 1					
										DATED 05/02/2013					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: RADAR REQUIRED.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS.

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

CITY AND STATE

DALLAS-FORT WORTH, TX

ELEVATION: 607

TDZE: 607

AIRPORT NAME:

DALLAS/FORT WORTH INTL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18R, AMDT 1A

18 SEPTEMBER 2014

SUP:

AMDT: 1

DATED: 05/02/2013

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0  
SBAS SERVICE PROVIDER IDENTIFIER 0  
AIRPORT IDENTIFIER KDFW  
RUNWAY RW18R  
APPROACH PERFORMANCE DESIGNATOR 0  
ROUTE INDICATOR  
REFERENCE PATH DATA SELECTOR 0  
REFERENCE PATH IDENTIFIER (APPROACH ID) W18B  
LTP/FTP LATITUDE 325456.9330N  
LTP/FTP LONGITUDE 0970316.7105W  
LTP/FTP ELLIPSOIDAL HEIGHT +01577  
FPAP LATITUDE 325244.3500N  
FPAP LONGITUDE 0970317.3985W  
THRESHOLD CROSSING HEIGHT (TCH) 00058.6  
TCH UNITS SELECTOR (METERS OR FEET USED) F  
GLIDEPATH ANGLE (GPA) 03.00  
COURSE WIDTH AT THRESHOLD 115.00  
LENGTH OFFSET 0000  
HORIZONTAL ALERT LIMIT (HAL) 40.0  
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

98B3752C

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4  
LTP ORTHOMETRIC HEIGHT +01849  
FPAP ORTHOMETRIC HEIGHT +01849

CITY AND STATE

DALLAS-FORT WORTH, TX

ELEVATION: 607

TDZE: 607

AIRPORT NAME:

DALLAS/FORT WORTH INTL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18R, AMDT 1A

18 SEPTEMBER 2014

SUP:

AMDT: 1

DATED: 05/02/2013

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KDFWK4FR18R	R	010	ICKELK4EA0E	I	IF			+ 04000	18000		A	JS
SUSAP	KDFWK4FR18R	R	011	YOHANK4EA0E	S	051TF	17630032		+ 03000			A	JS
SUSAP	KDFWK4FR18R	R	012	LEGREK4EA0E	S	051TF	17630063		+ 03000			A	JS
SUSAP	KDFWK4FR18R	R	020	NETEEK4EA1E	F	051TF	17630021		+ 02400		RW18R	K4PGA	JS
SUSAP	KDFWK4FR18R	R	020	NETEEK4EA2WALPV		ALNAV/VNAV	ALNAV						JS
SUSAP	KDFWK4FR18R	R	030	RW18RK4PGOGY	M	031TF	17630055	00665		-300		A	JS
SUSAP	KDFWK4FR18R	R	040		0	M	CA	1763	+ 01100			A	JS
SUSAP	KDFWK4FR18R	R	050	LIKESK4EA0EY	R	DF			+ 03000			A	JS
SUSAP	KDFWK4FR18R	R	060	LIKESK4EA0EE	R	HM	22400040		+ 03000			A	JS

[illegible][illegible][illegible]

CITY AND STATE <b>DALLAS-FORT WORTH, TX</b>	ELEVATION: <b>607</b>	TDZE: <b>607</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: <b>RNAV (GPS) RWY 18R, AMDT 1A</b> 18 SEPTEMBER 2014	SUP:
	AIRPORT NAME: <b>DALLAS/FORT WORTH INTL</b>	FACILITY IDENTIFIER: <b>RNAV</b>		AMDT: <b>1</b>
				DATED: <b>05/02/2013</b>

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		ICKEL	010	FACF	IF		FB				AA 04000	
		YOHAN	011	SDF	TF		FB	0.5	176.3 (180.3T)	003.2	AA 03000	
		LEGRE	012	SDF	TF		FB	0.5	176.3 (180.3T)	006.3	AA 03000	
		NETEE	020	FAF	TF		FB	0.5	176.3 (180.3T)	002.1	AA 02400	
		RW18R	030	MAP	TF		FO	0.3	176.3 (180.3T)	005.5	AT 00665	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		176.3 (180.3T)		AA 01100	
	LIKES	050		DF	R	FO				AA 03000	
	LIKES	060		HM	R	FO		224.0 (228.0T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ICKEL	N331155.29	W0970311.43	N3311.922	W09703.191
	LEGRE	N330227.81	W0970314.38	N3302.464	W09703.240
	LIKES	N323512.99	W0973430.14	N3235.217	W09734.502
	NETEE	N330024.40	W0970315.01	N3300.407	W09703.250
	YOHAN	N330845.93	W0970312.42	N3308.766	W09703.207
	RW18R	N325456.93	W0970316.71	N3254.949	W09703.279

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18R	00607	59

QUALITY  
CHECKED

CITY AND STATE  
DALLAS-FORT WORTH, TX

ELEVATION: 607 TDZE: 607  
 AIRPORT NAME:  
 DALLAS/FORT WORTH INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  
 RNAV (GPS) RWY 18R, AMDT 1A  
 18 SEPTEMBER 2014

SUP:  
 AMDT: 1  
 DATED: 05/02/2013