

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION <b>NDB      STANDARD INSTRUMENT APPROACH PROCEDURE</b> FLIGHT STANDARDS SERVICE - FAR PART 97. 27					Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES					MISSED APPROACH										
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: HHW NDB  CLIMB TO 2300 THEN LEFT TURN DIRECT HHW NDB AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD S, LT, 002 INBOUND FAS OBST: 910 TOWER 340040/953328  FAC CROSSES RWY C/L EXTENDED 3002 FROM THLD.											
MLC VORTAC	HHW NDB	157.98/49.98	3000												
PRX VOR/DME	HHW NDB	344.32/30.13	2300												
1. PT <u>R</u> SIDE OF COURSE <u>182.02</u> OUTBOUND <u>2300</u> FT WITHIN <u>10</u> MILES OF <u>HHW NDB</u> (IAF) 2. _____ 3. FAC <u>002.02</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: <u>HHW NDB 015 - 195 2500, 195 - 015 2200</u>					MAG VAR: 5E      EPOCH YEAR: 1990										
MINIMUMS															
TAKEOFF:	<input checked="" type="checkbox"/>	STANDARD	SEE FAA FORM 8260-15 FOR THIS AIRPORT				ALTERNATE:	<input type="checkbox"/>	<input checked="" type="checkbox"/>						
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-35	1280	1	689	1260	1	689		NA			NA				
CIRCLING	1260	1	689	1260	1	689		NA			NA				
NOTES:															
CITY AND STATE		ELEVATION: 571    TDZE: 571		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP					
HUGO, OK		STAN STAMPER MUNI		HHW		NDB OR GPS RWY 35, AMDT 1 31 DEC 98				AMDT      ORIG					
										DATED      30 APR 92					