

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: PSC VOR/DME						
PSC VOR/DME		RASPY/PSC 6.00 DME		036.83 / 6.00				3200		CLIMBING LEFT TURN TO 3200 ON HEADING 080 AND ON PSC VOR/DME R-092 TO CITYS INT/PSC 14.00 DME AND HOLD.						
GUSSE/PSC 14.00 DME CW (IAF)		DMAGY/PSC 14.00 DME (NOPT)		14.00 DME ARC				3200								
EXODE/PSC 14.00 DME CW (IAF)		DMAGY/PSC 14.00 DME (NOPT)		14.00 DME ARC				3200								
CITYS INT/PSC 14.00 DME CCW (IAF)		DMAGY/PSC 14.00 DME (NOPT)		14.00 DME ARC				3200								
DMAGY/PSC 14.00 DME (IF)		RASPY/PSC 6.00 DME		216.83 / 8.00 (PSC R-037)				2300		ADDITIONAL FLIGHT DATA: HOLD E, RT, 272.44 INBOUND. CHART FAS OBST: 635 TWR 461730N/1190413W AAO 922 462027N/1190130W CHART VDP AT 1.49 DME DISTANCE VDP TO THLD 1.39 MILES. CHART PSC BRG-273 AT GUSSE. CHART PSC BRG-306 AT EXODE. CHART PSC BRG-092 AT CITYS. CHART CIRCLING ICON RASPY TO RW21R: 2.95/54 FAC CROSSES RWY C/L EXTENDED 7749 FROM THLD.						
1. PT <u> L </u> SIDE OF COURSE <u> 036.83 </u> OUTBOUND <u> 3200 </u> FT WITHIN <u> 10 </u> MILES OF <u> RASPY </u> (IAF)																
2. _____																
3. FAC <u> 216.83 </u> FAF RASPY/PSC 6.00 DME DIST FAF TO MAP _____ THLD <u> 5.90 </u>																
4. MIN. ALT <u> RASPY 2300, FAMES/PSC 3.00 DME 1360 </u>																
8. MSA FROM: PSC VOR/DME 100-190 3500, 190-300 4800, 300-100 2900										MAG VAR: 15E		EPOCH YEAR:2015				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY ==>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-21R	900	2400	496	900	2400	496	900	5000	496	900	5000	496				
CIRCLING	900	1	490	940	1	530	1040	1 3/4	630	1100	2 1/4	690				
NOTES: CHART NOTE: VDP NA WITH HERMISTON ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HERMISTON ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND INCREASE S-21R CAT C AND D AND CIRCLING CAT C/D VISIBILITY 1/4 MILE. CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-21R CAT C/D VISIBILITY TO 1 3/8 MILE.																
CITY AND STATE PASCO, WA		ELEVATION: 410 AIRPORT NAME: TRI-CITIES		TDZE: 404		FACILITY IDENTIFIER: PSC		PROCEDURE NO./AMDТ NO./EFFECTIVE DATE: VOR/DME RWY 21R, AMDT 7, 11/13/2014				SUP				
												AMDT 6				
												DATE 11/18/2010				