U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
OLU VOR/DME	SCB VOR/DME	065.58 / 33.41	3100
KENAR INT	SCB VOR/DME	297.13 / 16.10	3000

MISSED APPROACH

MAP: SCB VOR/DME

CLIMB TO 3000, THEN RIGHT TURN DIRECT SCB VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD N, RT, 161.00 INBOUND

FAS OBST: 1465 TREE 413318 / 0963854

FAROD TO RWY 35: 3.02/40

CHART 1801 TOWER 412502 / 0963817

CHART 1719 TOWER 412440 / 0963158

FAC CROSSES RWY C/L 4878' FROM THLD

MAG VAR: 6E EPOCH YEAR: 1995

1. PT L SIDE OF COURSE 161.00 OUTBOUND 3000 FT WITHIN 10 MILES OF SCB VOR/DME (IAF)
2.
3. FAC 341.00 FAF DIST FAF TO MAP THLD
4. MIN. ALT FAROD INT/SCB 1.70 DME 1940
8. MSA FROM: SCB VOR/DME 090-180 2900, 180-090 3300

MINIMUMS

TAKEOFF: X STANDARD SEE FAA FORM 8260-15 FOR THIS AIRPORT ALTERNATE: N A X

CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/	MDA	VIS	HAT/	MDA	VIS	HAT/	MDA	VIS	HAT/
S-35	1940	1	621	1940	1	621		NA			NA				
CIRCLING	1940	1	615	1940	1	615		NA			NA				
FAROD FIX MINIMUMS															
S-35	1800	1	481	1800	1	481		NA			NA				
CIRCLING	1900	1	575	1900	1	575		NA			NA				

NOTES:
USE FREMONT ALTIMETER SETTING

CITY AND STATE	ELEVATION: 1325 TDZE: 1319 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP
SCRIBNER, NE	SCRIBNER STATE	SCB	NOV 2 8 2002 VOR RWY 35, AMDT 2	AMDT 1
				DATED 09 OCT 97