

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW13 LNAV: RW13 CLIMB TO 2000 DIRECT LEYIC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 320.29 INBOUND. FAS OBST: 200 SHIP 270530N/0822750W FAS OBST: 200 SHIP 270432N/0822713W WAAS CHANNEL # 86423 REFERENCE PATH ID: W13A JIVGA TO RW13: 3.00/46. LTP HAE: -19.4 M											
FOVTA (IF/IAF)	JIVGA (FB)	140.14 / 6.76	1600												
JIVGA (FAF)	RW13 (MAP) (FO)	140.18 / 4.83													
RW13 (MAP)	418 MSL	140.18													
418 MSL	LEYIC (FO)		2000												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW FOVTA, RT, 140.14 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>140.18</u> FAF: <u>JIVGA</u> DIST FAF TO MAP: <u>4.83</u> THLD: <u>4.83</u> 4. MIN. ALT: <u>FOVTA 2000, JIVGA 1600</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 5W EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY <u> </u>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	460	1	445	460	1	445	460	1 3/8	445	460	1 3/8	445			
LNAV MDA	460	1	445	460	1	445	460	1 3/8	445	460	1 3/8	445			
CIRCLING	500	1	482	500	1	482	500	1 1/2	482	600	2	582			
NOTES: CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 31 NA AT NIGHT. CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. (SEE FORM 8260-10)															
CITY AND STATE			ELEVATION: 18 THRE: 15			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
VENICE, FL			AIRPORT NAME: VENICE MUNI			RNAV			RNAV (GPS) RWY 13, AMDT 1 30 JUN 2011			AMDT: ORIG DATED 09/25/2008			

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SARASOTA ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.

TAA

	FROM	TO	ALT
1.	050/30 CW 230/30 (NOPT)	FOVTA (IF/IAF) (FB)	2000
2.	230/30 CW 050/30	230/20 CW 050/20	2800
3.	230/20 CW 050/20	FOVTA (IF/IAF) (FO)	2000

QUALITY
6
CHECKED

CITY AND STATE

VENICE, FL

ELEVATION: 18

THRE: 15

AIRPORT NAME:

VENICE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, AMDT 1

30 JUN 2011

SUP:

AMDT: ORIG

DATED: 09/25/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KVNC
RUNWAY	RW13
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W13A
LTP/FTP LATITUDE	270434.1680N
LTP/FTP LONGITUDE	0822648.7910W
LTP/FTP ELLIPSOIDAL HEIGHT	-00194
FPAP LATITUDE	270330.7500N
FPAP LONGITUDE	0822538.4800W
THRESHOLD CROSSING HEIGHT (TCH)	00046.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

DF1E454F

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00045
FPAP ORTHOMETRIC HEIGHT	+00045

CITY AND STATE
VENICE, FL

ELEVATION: 18 THRE: 15
AIRPORT NAME:
VENICE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 13, AMDT 1
30 JUN 2011

SUP:
AMDT: ORIG
DATED: 09/25/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KVNCK7FR13	AFOVTA	010FOVTAK7EA0EE	AR	HF			14010040	+ 02000	18000			A JS	
SUSAP KVNCK7FR13	R	010FOVTAK7EA0E	I	IF				+ 02000	18000			A JS	
SUSAP KVNCK7FR13	R	020JIVGAK7EA1E	F	051TF			14010068	+ 01600				A JS	
SUSAP KVNCK7FR13	R	020JIVGAK7EA2WALP			N	ALNAV						JS	
SUSAP KVNCK7FR13	R	030RW13 K7PGOGY	M	031TF			14020048	00061		-300		A JS	
SUSAP KVNCK7FR13	R	040	0	M	CA		1402	+ 00418				A JS	
SUSAP KVNCK7FR13	R	050LEYICK7EA0EY		DF				+ 02000				A JS	
SUSAP KVNCK7FR13	R	060LEYICK7EA0EE	R	HM			32030040	+ 02000				A JS	

[illegible][illegible]

CITY AND STATE VENICE, FL	ELEVATION: 18 THRE: 15 AIRPORT NAME: VENICE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, AMDT 1 30 JUN 2011	SUP:	
				AMDT:	ORIG
				DATED:	09/25/2008