

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 5, 700-3 OR STANDARD WITH MINIMUM CLIMB OF 318 FEET PER NM TO 5100, OR...
RWY 14, 800-3 OR STANDARD WITH MINIMUM CLIMB OF 263 FEET PER NM TO 5100, OR...
RWY 23, 900-3 OR STANDARD WITH MINIMUM CLIMB OF 348 FEET PER NM TO 5100, OR...
RWY 32, STANDARD.

...1400/3 FOR CLIMB IN VISUAL CONDITIONS. CLIMB IN VISUAL CONDITIONS NA AT NIGHT.

(2) DEPARTURE PROCEDURE:

RWY 5 - CLIMBING LEFT TURN VIA SHR R-106 TO SHR VORTAC, OR CLIMB IN VISUAL CONDITIONS TO CROSS SHERIDAN COUNTY AIRPORT NORTHWESTBOUND AT OR ABOVE 5300, THEN VIA SHR R-126 TO SHR VORTAC, THENCE...
RWY 14 - CLIMBING LEFT TURN VIA HEADING 320 AND SHR R-106 TO SHR VORTAC, OR CLIMB IN VISUAL CONDITIONS TO CROSS SHERIDAN COUNTY AIRPORT NORTHWESTBOUND AT OR ABOVE 5300, THEN VIA SHR R-126 TO SHR VORTAC, THENCE...
RWY 23 - CLIMBING RIGHT TURN VIA SHR R-153 TO SHR VORTAC, OR CLIMB IN VISUAL CONDITIONS TO CROSS SHERIDAN COUNTY AIRPORT NORTHWESTBOUND AT OR ABOVE 5300, THEN VIA SHR R-126 TO SHR VORTAC, THENCE...
RWY 32 - CLIMB VIA HEADING 320 AND SHR R-106 TO SHR VORTAC, THENCE...

...CLIMB IN HOLDING PATTERN (HOLD NW, LT, 133.00 INBOUND) TO CROSS SHR VORTAC AT OR ABOVE AIRWAY MEA FOR ROUTE OF FLIGHT.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 5, MULTIPLE TREES BEGINNING 101 FEET FROM DER, 188 FEET LEFT OF CENTERLINE, UP TO 80 FEET AGL/3991 FEET MSL.
NOTE: RWY 23, FENCE 1201 FEET FROM DER, 10 FEET LEFT OF CENTERLINE, 20 FEET AGL/4060 FEET MSL. BUILDING 1949 FEET FROM DER, 415 FEET LEFT OF CENTERLINE, 17 FEET AGL/4077 FEET MSL. TREE 3337 FEET FROM DER, 391 FEET RIGHT OF CENTERLINE, 43 FEET AGL/4143 FEET MSL.
NOTE: RWY 32, ANTENNA 53 FEET FROM DER, 398 FEET RIGHT OF CENTERLINE, 20 FEET AGL/4020 FEET MSL.

(4) CONTROLLING OBSTACLES:

RWY 5: 3991 MSL TREE 444638.76/1065811.71, 3988 MSL TREE 444639.20/1065806.44, 3979 MSL TREE 444638.45/1065801.22, 4653 MSL TOWER 444712.00/1065309.00. RWY 14: 4459 MSL AAO 444334.29/1065459.14, 4529 MSL AAO 444253.45/1065514.03, 4599 MSL AAO 444248.74/1065508.81, 4619 MSL AAO 444246.31/1065453.58, 4699 MSL AAO 444221.92/1065455.26, 4779 MSL AAO 444238.69/1065412.91. RWY 23: 4060 MSL FENCE 444610.63/1065930.53, 4077 MSL BLDG 444604.15/1065938.04, 4143 MSL TREE 444606.39/1070000.07, 4190 MSL TREE 444551.57/1070009.40, 4186 MSL TERRAIN 444600.96/1070016.00, 4202 MSL FENCE 444544.97/1070007.51, 4217 MSL OL ON POLE 444544.54/1070011.70, (CONTINUED ON PG 2)

(5) City, State

SHERIDAN, WY

(6) Airport

SHERIDAN COUNTY

(7) Effective Date

MAR 15 2007

(8) Amdt. No.

3

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

(2) DEPARTURE PROCEDURE:

(3) TAKEOFF OBSTACLE NOTES:

(4) CONTROLLING OBSTACLES:

(CONT) 4250 MSL OL ON POLE 444540.06/1070011.66, 4195 MSL TERRAIN 444552.14/1070019.59, 4258 MSL OL ON POLE 444544.64/1070034.23, 4220 MSL TERRAIN 444543.17/1070044.89, 4278 MSL POLE 444550.16/1070052.56, 4224 MSL TERRAIN 444555.77/1070055.35, 4245 MSL TERRAIN 444536.26/1070057.10, 4263 MSL FENCE 444530.92/1070056.09, 4264 MSL TERRAIN 444545.37/1070110.10, 4400 MSL TERRAIN 444457.72/1070145.62, 4424 MSL SCRUB 444451.00/1070148.00, 4825 MSL AAO 444431.02/1070316.86. RWY 32: 4020 MSL ANTENNA 444639.37/1065911.16.

(5) City, State

SHERIDAN, WY

(6) Airport

SHERIDAN COUNTY

(7) Effective Date

MAR 15 2007

(8) Amdt. No.

3

