

## DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH:

ATA ☒ AAT ☐ ALPA ☒ APA ☒ AOP ☒ NBA ☒ OTHER (specify) ☒ ZBW, BGR FSS, AIRPORT MANAGER

TAKEOFF MINIMUMS:

RWY 15 - STANDARD

RWY 33 - 300-1 OR STANDARD WITH MINIMUM CLIMB OF 240' PER NM TO 300'



IFR DEPARTURE PROCEDURE:

TAKEOFF OBSTACLES:

RWY 33 - 147 TREE 445458/670140

DEPARTURE OBSTACLES:

\* CONCURRENT WITH NDB RWY 15, ORIGINAL AND NDB RWY 33, ORIGINAL.

DEVELOPED BY		APPROVED BY	
SIGNATURE:  RUSSELL D. JONES (BEGUE)	DATE: 10/6/93 FIFO: AVN-830	SIGNATURE:  LARRY F. GRINDROD	DATE: 10/7/93 FIFO: AVN-830
CITY AND STATE EASTPORT, ME	AIRPORT EASTPORT MUNI	EFFECTIVE DATE 6/23/94	AMDT. NO. 0