

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
<b>TERMINAL ROUTES</b>								<b>MISSED APPROACH</b>				
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW08  CLIMB TO 2000 DIRECT FORSU AND HOLD.  <b>ADDITIONAL FLIGHT DATA:</b> HOLD E, RT, 270.88 INBOUND. CHART FAS OBST: 409 TWR 261047N/0801315W CHART 219 AAO 261122N/0801550W. CHART A-291A. CHART A-291B. CHART A-291C. DISTANCE TO THLD FROM 200 HAT: 0.45 NM. CHART VDP AT 1.30 MILES TO RW08* *LNAV ONLY. WAAS CHANNEL # 48919 REFERENCE PATH ID: W08A LTP HAE: -22 M CHART CIRCLING ICON. CHART KPMP.  MAG VAR: 7W                      EPOCH YEAR: 2015				
ENVER (IF/IAF)		PADDS (FB)		090.68 / 6.14		2000						
PADDS (FAF)		TRUBE/3.00 NM TO RW08 (FB)		090.73 / 3.07								
TRUBE/3.00 NM TO RW08		RW08 (MAP) (FO)		090.73 / 3.00								
RW08 (MAP)		213 MSL		090.73		2000						
213 MSL		FORSU (FO)										
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD W ENVER, LT, 090.68 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 090.73    FAF: PADDS                      DIST FAF TO MAP: 6.07    THLD: 6.07 4. MIN. ALT: ENVER 2000, PADDS 2000, TRUBE/3.00 NM TO RW08 1020* 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: 2000    GS ALT AT: PADDS 2000                      OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: 3.00    TCH: 55.4 34:1 IS CLEAR 8. MSA FROM: RW08 2600												
<b>MINIMUMS</b>												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		# STANDARD				
CATEGORY ==>		A		B		C		D		E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	213	1/2	200	213	1/2	200	213	1/2	200	213	1/2	200
LNAV/VNAV DA	427	7/8	414	427	7/8	414	427	7/8	414	427	7/8	414
LNAV MDA	480	1/2	467	480	1/2	467	480	1	467	480	1	467
CIRCLING	520	1	507	620	1	607	780	2 1/4	767	780	2 1/2	767
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 4C (40F) OR ABOVE 54C (130F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FORT LAUDERDALE/HOLLYWOOD INTL ALTIMETER SETTING AND INCREASE LPV DA TO 231; LNAV/VNAV DA TO 445. INCREASE ALL MDA 20 FEET. INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING FORT LAUDERDALE/HOLLYWOOD INTL ALTIMETER SETTING. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: RADAR REQUIRED. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT ENVER ON V267-437 SOUTHEAST BOUND.												
CITY AND STATE		ELEVATION: 13      TDZE: 13		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
FORT LAUDERDALE, FL		AIRPORT NAME:  FORT LAUDERDALE EXECUTIVE				RNAV (GPS) RWY 8, AMDT 2 18 SEPTEMBER 2014				AMDT: 1		
										DATED 09/23/2010		

 QUALITY  
9  
CHECKED

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0  
SBAS SERVICE PROVIDER IDENTIFIER 0  
AIRPORT IDENTIFIER KFXE  
RUNWAY RW08  
APPROACH PERFORMANCE DESIGNATOR 0  
ROUTE INDICATOR  
REFERENCE PATH DATA SELECTOR 0  
REFERENCE PATH IDENTIFIER (APPROACH ID) W08A  
LTP/FTP LATITUDE 261151.2680N  
LTP/FTP LONGITUDE 0801051.1155W  
LTP/FTP ELLIPSOIDAL HEIGHT -00220  
FPAP LATITUDE 261200.9400N  
FPAP LONGITUDE 0800912.6400W  
THRESHOLD CROSSING HEIGHT (TCH) 00055.4  
TCH UNITS SELECTOR (METERS OR FEET USED) F  
GLIDEPATH ANGLE (GPA) 03.00  
COURSE WIDTH AT THRESHOLD 106.75  
LENGTH OFFSET 0920  
HORIZONTAL ALERT LIMIT (HAL) 40.0  
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

12C44726

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K7  
LTP ORTHOMETRIC HEIGHT +00036  
FPAP ORTHOMETRIC HEIGHT +00036

CITY AND STATE

FORT LAUDERDALE, FL

ELEVATION: 13

TDZE: 13

AIRPORT NAME:

FORT LAUDERDALE EXECUTIVE

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 8, AMDT 2  
18 SEPTEMBER 2014

SUP:

AMDT: 1

DATED: 09/23/2010



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KFXEK7FR08	AENVER	010ENVERK7EA0EE	AL	HF		09070040	+	02000	18000		A	JS
SUSAP	KFXEK7FR08	R	010ENVERK7EA0E	I	IF			+	02000	18000		A	JS
SUSAP	KFXEK7FR08	R	020PADDSK7EA1E	F	051TF		09070061	+	02000		RW08	K7PGA	JS
SUSAP	KFXEK7FR08	R	020PADDSK7EA2WALPV			ALNAV/VNAV							JS
SUSAP	KFXEK7FR08	R	021TRUBEK7EA0E	S	031TF		09070031	V	0102001030		-300		A JS
SUSAP	KFXEK7FR08	R	030RW08	K7PG0GY	M	031TF	09070030		00067		-300		A JS
SUSAP	KFXEK7FR08	R	040		C	M	0907	+	00213				A JS
SUSAP	KFXEK7FR08	R	050FORSUK7EA0EY		DF			+	02000				A JS
SUSAP	KFXEK7FR08	R	060FORSUK7EA0EE	R	HM		27090040	+	02000				A JS

[illegible][illegible][illegible]

CITY AND STATE <b>FORT LAUDERDALE, FL</b>	ELEVATION: <b>13</b> AIRPORT NAME: <b>FORT LAUDERDALE EXECUTIVE</b>	TDZE: <b>13</b>  <b>RNAV</b>	FACILITY IDENTIFIER:  <b>RNAV</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: <b>RNAV (GPS) RWY 8, AMDT 2</b> 18 SEPTEMBER 2014	SUP:
					AMDT: <b>1</b>
					DATED: <b>09/23/2010</b>

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	ENVER	ENVER	010	IAF	HP	L	FO		090.7(083.7T)	004.0	AA 02000	
		ENVER	010	FACF	IF		FB				AA 02000	
		PADDS	020	FAF	TF		FB	0.5	090.7(083.7T)	006.1	AA 02000	
		TRUBE	021	SDF	TF		FB	0.3	090.7(083.7T)	003.1	AA 01020	GS 01030
		RW08	030	MAP	TF		FO	0.3	090.7(083.7T)	003.0	AT 00067	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		090.7(083.7T)		AA 00213	
	FORSU	050		DF		FO				AA 02000	
	FORSU	060		HM	R	FO		270.9(263.9T)	004.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ENVER	N261030.98	W0802420.77	N2610.516	W08024.346
	FORSU	N261306.23	W0795802.55	N2613.104	W07958.043
	PADDS	N261111.54	W0801733.58	N2611.192	W08017.560
	TRUBE	N261131.67	W0801410.05	N2611.528	W08014.168
	RW08	N261151.27	W0801051.12	N2611.855	W08010.852

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW08	00012	55

CITY AND STATE FORT LAUDERDALE, FL	ELEVATION: 13	TDZE: 13	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:		RNAV	RNAV (GPS) RWY 8, AMDT 2	AMDT: 1
	FORT LAUDERDALE EXECUTIVE			18 SEPTEMBER 2014	DATED: 09/23/2010