

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 3.09 MILES AFTER KIBBY INT/6.01 DME OR AT 9.10 DME FIX					
PMM VOR/DME (IF/IAF)		KIBBY INT/6.01 DME		224.31 / 6.01				1700		CLIMBING TO 2500 THEN CLIMBING LEFT TURN TO 4000 DIRECT PMM VOR/DME AND HOLD.					
										ADDITIONAL FLIGHT DATA: FAS OBST: 869 AAO 422339N/0860939W KIBBY TO RW23: 3.03/40. CHART CIRCLING ICON					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE PMM VOR/DME, RT, 224.31 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC 224.31 FAF KIBBY INT/6.01 DME _____ DIST FAF TO MAP 3.09 THLD 3.09 4. MIN. ALT PMM VOR/DME 2500, KIBBY 1700 8. MSA FROM: PMM VOR/DME 360-180 3000, 180-360 2400										MAG VAR: 0E		EPOCH YEAR: 1965			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY ==>		A		B		C		D		E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-23	1120	1	454	1120	1	454	1120	1 3/8	454	1120	1 3/8	454			
CIRCLING	1120	1	454	1140	1	474	1280	1 3/4	614	1520	2 3/4	854			
NOTES: CHART NOTE: PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON PMM VOR/DME AIRWAY RADIALS 303 CW 112. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BENTON HARBOR ALTIMETER SETTING; (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 666 TDZE: 666		FACILITY IDENTIFIER: PMM		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP		VOR RWY 22			
SOUTH HAVEN, MI		AIRPORT NAME:		SOUTH HAVEN AREA RGNL		VOR RWY 23, AMDT 11A 13 NOVEMBER 2014				AMDT		11			
										DATE		05/05/2011			

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):****INCREASE ALL MDA 40 FEET AND CIRCLING CAT D VISIBILITY 1/4 MILE.****CHART NOTE: CIRCLING NA TO RWYS 14 AND 32.****CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.**

CITY AND STATE

SOUTH HAVEN, MI

ELEVATION: 666

TDZE: 666

AIRPORT NAME:

SOUTH HAVEN AREA RGNL

FACILITY  
IDENTIFIER:

PMM

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 23, AMDT 11A

13 NOVEMBER 2014

SUP: VOR RWY 22

AMDT: 11

DATED: 05/05/2011