

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH					
FROM			TO			COURSE AND DISTANCE			ALTITUDE			RNP: DA CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3500 DIRECT TROYS AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 185.00 INBOUND. DISTANCE TO THLD FROM 412 HAT: 1.12 NM. ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S ROUTE TYPE: A, H #TCH 1044.6 MSL (DO NOT CHART) CHART MANDATORY 8000 AT BROOX. CHART MINIMUM 5000 AT HAINZ.					
HAINZ (IAF)			BAMBU (TF) (FB) (RNP 1.00)			275.14 / 3.77			4000								
BROOX (IAF)			OLEGG (TF) (FB) (RNP 1.00)			094.99 / 6.29			6000								
OLEGG			BAMBU (RF) (FB) (RNP 1.00)			(2.50 NM RADIUS CW (CFZJB))/7.86			4000								
BAMBU (IF)			AJAAY (TF) (FB) (RNP 1.00)			275.10 / 5.01			2700								
AJAAY (FAF)			RW26R (MAP) (TF) (FO) (RNP 0.30)			275.05 / 5.20											
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT BAMBU 3. FAC: 275.05 FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: BAMBU 4000, AJAAY 2700 5. DIST TO THLD FROM OM: 5.20 MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2700 GS ALT AT: AJAAY 2700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 54.6 # 34:1 IS CLEAR 8. MSA FROM: RW26R 3100																	
												MAG VAR: 5W			EPOCH YEAR: 2015		
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD					
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
AUTHORIZATION REQUIRED																	
RNP 0.30 DA	1402	4500	412	1402	4500	412	1402	4500	412	1402	4500	412					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -8C (18F) OR ABOVE 54C (130F). CHART NOTE: GPS REQUIRED. CHART SPEED ICON IN PLANVIEW AT OLEGG : MAX 210 KIAS. CHART PLANVIEW NOTE ADJACENT TO BROOX IAF: RF REQUIRED. (CONTINUED ON PAGE 2)																	
CITY AND STATE				ELEVATION: 1026 TDZE: 990				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:	
ATLANTA, GA				AIRPORT NAME:								RNAV (RNP) Z RWY 26R, AMDT 1				AMDT: ORIG	
				HARTSFIELD - JACKSON ATLANTA INTL								12 OCTOBER 2017				DATED 09/18/2014	



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT , HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33																
TERMINAL ROUTES, (CONT.):																
<table><tr><td>FROM</td><td>TO</td><td>COURSE AND DISTANCE</td><td>ALTITUDE</td></tr><tr><td>RW26R (MAP)</td><td>1500 MSL (CA)</td><td>275.05</td><td>1500</td></tr><tr><td>1500 MSL</td><td>TROYS (DF) (FO) (RNP 1.00)</td><td></td><td>3500</td></tr></table>					FROM	TO	COURSE AND DISTANCE	ALTITUDE	RW26R (MAP)	1500 MSL (CA)	275.05	1500	1500 MSL	TROYS (DF) (FO) (RNP 1.00)		3500
FROM	TO	COURSE AND DISTANCE	ALTITUDE													
RW26R (MAP)	1500 MSL (CA)	275.05	1500													
1500 MSL	TROYS (DF) (FO) (RNP 1.00)		3500													
NOTES, (CONT.): CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. ARRIVAL FROM BROOX NA DURING SIMULTANEOUS TRIPLE APPROACHES.																
<div>QUALITY 20 CHECKED</div>																
CITY AND STATE ATLANTA, GA	ELEVATION: 1026 AIRPORT NAME: HARTSFIELD - JACKSON ATLANTA INTL	TDZE: 990	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 26R, AMDT 1 12 OCTOBER 2017												
				SUP:												
				AMDT: ORIG												
				DATED: 09/18/2014												