

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
FEDMU (IAF)	ENEPE (FB)	190.97 / 10.59	3500	LPV: DA LNAV/VNAV: DA LNAV: RW14											
AQUAT (IAF)	ENEPE (FB)	094.29 / 11.56	3500												
ENEPE (IF)	CEGTU (FB)	140.93 / 6.21	2700	CLIMB TO 3500 DIRECT WUNTA AND HOLD.											
CEGTU (FAF)	DUBKE/3.00 NM TO RW14 (FB)	141.00 / 2.19													
DUBKE/3.00 NM TO RW14	RW14 (MAP) (FO)	141.02 / 3.00		ADDITIONAL FLIGHT DATA: HOLD SE, RT, 321.18 INBOUND. CHART FAS OBST: 1179 TREE 451134N/0923406W CHART FAS OBST: 1139 TREE 450921N/0923330W DISTANCE TO THLD FROM 274 HATH: 0.70 NM. WAAS CHANNEL # 82425 REFERENCE PATH ID: W14A LTP HAE: 274.9 M											
RW14 (MAP)	1272 MSL	141.02													
1272 MSL	WUNTA (FO)		3500												
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. PROFILE STARTS AT ENEPE 3. FAC: 141.00 FAF: CEGTU DIST FAF TO MAP: 5.19 THLD: 5.19 4. MIN. ALT: ENEPE 3500, CEGTU 2700, DUBKE/3.00 NM TO RW14 2000* 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 2700 GS ALT AT: CEGTU 2700 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS NOT CLEAR 8. MSA FROM: RW14 3500								MAG VAR: 2E	EPOCH YEAR: 1995						
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1272	1	274	1272	1	274	1272	1	274	1272	1	274			
LNAV/VNAV DA	1320	1	322	1320	1	322	1320	1	322	1320	1	322			
LNAV MDA	1440	1	442	1440	1	442	1440	1 3/8	442	1440	1 3/8	442			
CIRCLING	1520	1	522	1520	1	522	1520	1 1/2	522	1560	2	562			
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING OSCEOLA ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 37C (98F). CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 14 PROCEDURE NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 998 THRE: 998		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
NEW RICHMOND, WI		AIRPORT NAME:				RNAV (GPS) RWY 14, AMDT 2A				AMDT: 2					
		NEW RICHMOND RGNL				15 DEC 2011				DATED		10/20/2011			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OSCEOLA ALTIMETER SETTING AND INCREASE ALL DA/MDA 40 FEET; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE.



CITY AND STATE NEW RICHMOND, WI	ELEVATION: 998	THRE: 998	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 14, AMDT 2A 15 DEC 2011	SUP:
	AIRPORT NAME: NEW RICHMOND RGNL				AMDT: 2
					DATED: 10/20/2011

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRNH
RUNWAY	RW14
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W14A
LTP/FTP LATITUDE	450921.5845N
LTP/FTP LONGITUDE	0923246.4245W
LTP/FTP ELLIPSOIDAL HEIGHT	+02749
FPAP LATITUDE	450810.3800N
FPAP LONGITUDE	0923130.7600W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

5ADD38AD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+03040
FPAP ORTHOMETRIC HEIGHT	+03040

CITY AND STATE

NEW RICHMOND, WI

ELEVATION: 998

THRE: 998

AIRPORT NAME:

NEW RICHMOND RGNL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 14, AMDT 2A

15 DEC 2011

SUP:

AMDT:

2

DATED:

10/20/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	2
DATED:	10/20/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	2
DATED:	10/20/2011