

U.S. Department of Transportation  
Federal Aviation Administration

**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE**  
**TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
BYP VORTAC (40V)	IMOPY (TF) (FB) (40E) (41E)	173.43/45.36	2500	LNAV: RW35L											
CQY VORTAC (40V) (43A) (IAF)	IMOPY (NOPT) (TF) (FB) (40E) (41E) (43B)	353.43/35.59	2500	CLIMB TO 2500 DIRECT IGATE AND HOLD											
IMOPY (IF/IAF) (40E) (43I)	KOGLY (TF) (FB) (40E) (43F)	347.57/10.00	2200												
RW35L (MAP) (40G) (41Y) (43M)	942 MSL (CA) (42M)	355.10													
942 MSL	IGATE (DF) (FO) (40E) (41E) (43H)		2500												
This is a corrected copy of a procedure published in TL 05-08.				ADDITIONAL FLIGHT DATA: HOLD N, LT, 175.10 INBOUND FAS OBST: 637 TREE 330141N/0961419W CHART 760 WATER TOWER 325941N/0961502W KOGLY TO RW35L: 3.04/40 ROUTE TYPE DESCRIPTION: A, P APPROACH ROUTE QUALIFIER 2: S											
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)															
2. HOLD S IMOPY, RT, 347.57 INBOUND, 2500 FT IN LIEU OF PT (IAF) (40E) (41E) (43C)															
3. FAC: 355.10 FAF: KOGLY DIST FAF TO MAP: 5.03 THLD: 5.03															
4. MIN. ALT: IMOPY 2500, KOGLY 2200, MUMGE/1.88 NM TO RW35L (40E) (42S) 1180															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:															
7. GS ANGLE: TCH: 34:1 IS CLEAR															
8. MSA FROM: RW35L 2600				MAG VAR: 6E EPOCH YEAR: 85											
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	X									
CATEGORY ==>	A		B		C		D	E							
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	980	1	439	980	1	439	980	1 1/4	439		NA				
CIRCLING	1040	1	498	1040	1	498	1040	1 1/2	498		NA				
NOTES: CHART NOTES: USE DALLAS-LOVE FIELD ALTIMETER SETTING, IF NOT RECEIVED USE DALLAS/FORT WORTH INTERNATIONAL ALTIMETER SETTING AND INCREASE ALL MDAs 20 FT. CIRCLING NA TO RWYs 17L/35R. DME/DME RNP-0.3 NA.															
CITY AND STATE		ELEVATION: 542 TDZE: 541		FACILITY IDENTIFIER: RNAV		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: MAY 12 2005		SUP: NONE							
CADD O MILLS, TX		CADD O MILLS MUNI				RNAV (GPS) RWY 35L, ORIG		DATE							