

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW07 CLIMB TO 2700 DIRECT HELEG AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 252.32 INBOUND. CHART FAS OBST: 769 TREE 414342N/0894222W CHART VDP AT 1.01 NM TO RW07. CHART CIRCLING ICON. JIGRO TO RW07: 3.00/49											
CVA VORTAC (IAF)	KEBEY (TF) (FB) (RNP 1.00)	096.45 / 25.28	2700												
GENSO (IAF)	KEBEY (TF) (FB) (RNP 1.00)	039.97 / 23.78	2700												
KEBEY (IF)	JIGRO (TF) (FB) (RNP 1.00)	071.98 / 6.03	2400												
JIGRO (FAF)	IROCI/1.90 NM TO RW07 (TF) (FB) (RNP 0.30)	072.07 / 3.45													
IROCI/1.90 NM TO RW07	RW07 (MAP) (TF) (FO) (RNP 0.30)	072.07 / 1.90													
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT KEBEY 3. FAC: <u>072.07</u> FAF: <u>JIGRO</u> DIST FAF TO MAP: <u>5.35</u> THLD: <u>5.35</u> 4. MIN. ALT: KEBEY 2700, JIGRO 2400, IROCI/1.90 NM TO RW07 1300 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW07 2500															
				MAG VAR: 2W EPOCH YEAR: 2020											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY >>>>>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1020	1	372	1020	1	372	1020	1	372	1020	1	372			
CIRCLING	1140	1	492	1140	1	492	1160	1 1/2	512	1480	2 3/4	832			
NOTES: CHART NOTE: CIRCLING RWY 36 NA AT NIGHT. CHART NOTE: RWY 7 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GENSO ON V8-38 WESTBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON CVA VORTAC AIRWAY RADIALS 057 CW 083.															
CITY AND STATE		ELEVATION: 648 TDZE: 648		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
STERLING/ROCKFALLS, IL		AIRPORT NAME:				RNAV (GPS) RWY 7, AMDT 1				AMDT: ORIG					
		WHITESIDE CO ARPT-JOS H BITTORF FLD				19 JULY 2018				DATED 11/20/2008					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW07 (MAP)	1020 MSL (CA)	072.07	
1020 MSL	HELEG (DF) (FO) (RNP 1.00)		2700

QUALITY
16
CHECKED

CITY AND STATE STERLING/ROCKFALLS, IL	ELEVATION: 648 AIRPORT NAME: WHITESIDE CO ARPT-JOS H BITTORF FLD	TDZE: 648	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 1 19 JULY 2018	SUP:
					AMDT: ORIG
					DATED: 11/20/2008