

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 8, 12, 30 STANDARD.

RWY 26, 700-3 OR STANDARD WITH A MINIMUM CLIMB OF 320 FEET PER NM TO 1000.

(2) TEXTUAL DEPARTURE PROCEDURE:

RWY 8- CLIMB TO 3000' VIA HEADING 072.58 AND MOD VOR/DME R-264 TO MOD VOR/DME BEFORE PROCEEDING ON COURSE.

RWY 26- CLIMBING RIGHT TURN TO 3000' VIA HEADING 150 AND MOD VOR/DME R-264 TO MOD VOR/DME BEFORE PROCEEDING ON COURSE.

RWY 30- CLIMBING RIGHT TURN TO 3000' VIA HEADING 150 TO INTERCEPT MOD VOR/DME R-264 TO MOD VOR/DME BEFORE PROCEEDING ON COURSE.

RWY 12- CLIMBING LEFT TURN TO 3000' TO INTERCEPT MOD VOR/DME R-264 TO MOD VOR/DME BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES:

RWY 8: TREE 472' FROM DER, 198' LEFT OF CENTERLINE, 50' AGL/194' MSL. FENCE 167' FROM DER, 8' RIGHT OF CENTERLINE, 25' AGL/176' MSL. VEHICLE ON ROAD 241' FROM DER, 412' LEFT OF CENTERLINE, 15' AGL/183' MSL. VEHICLES ON ROADS STARTING 241' FROM DER, 7' RIGHT OF CENTERLINE, UP TO 15' AGL/189' MSL. POLES STARTING 403' FROM DER, 204' LEFT OF CENTERLINE, UP TO 54' AGL/208' MSL. POLES STARTING 727' FROM DER, 49' RIGHT OF CENTERLINE, UP TO 54' AGL/212' MSL.

RWY 12: TREES STARTING 436' FROM DER, 251' RIGHT OF CENTERLINE, UP TO 72' AGL/253' MSL. CONVEYOR 1995' FROM DER, 504' LEFT OF CENTERLINE, 66' AGL/ 270' MSL. POLES STARTING 832' FROM DER, 396' RIGHT OF CENTERLINE, UP TO 56' AGL/ 240' MSL.

(4) CONTROLLING OBSTACLES:

RWY 26: 794 TREE 374056.35N-1213005.39W

QUALITY
1
CHECKED

(5) City, State TRACY, CA	(6) Airport TRACY MUNICIPAL	(7) Effective Date 22 OCT 2009	(8) Amdt. No. 3
-------------------------------------	---------------------------------------	--	---------------------------

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
DEPARTURE PROCEDURE (CONTINUATION) FAA FORM 8260-15A
FLIGHT STANDARDS SERVICE

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL..
Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport
elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in
statute miles or in feet RVR.

RWY 12 CONT: OBSTRUCITON LIGHT ON HOPPER 1934' FROM DER, 274' RIGHT OF CENTERLINE, 74' AGL/255' MSL. VEHICLES ON ROAD STARTING 133' FROM DER, 272' LEFT OF CENTERLINE, UP TO 15' AGL/206' MSL. FENCE 32' FROM DER 405' LEFT OF CENTERLINE, 25' AGL/194' MSL.

RWY 26: TREE 1173' FROM DER, 180' RIGHT OF CENTERLINE, 35' AGL/234' MSL. TREES STARTING 1067' FROM DER, 125' LEFT OF CENTERLINE, UP TO 35' AGL/794' MSL. VEHICLE ON ROAD 236' FROM DER, 150' LEFT OF CENTERLINE, 15' AGL/214' MSL. FENCE 69' FROM DER, 133' LEFT OF CENTERLINE, 23' AGL/203' MSL. RISING TERRAIN 11105' FROM DER, 2814' LEFT OF CENTERLINE, UP TO 739' MSL.

RWY 30: TREES STARTING 438' FROM DER, 30' RIGHT OF CENTERLINE, UP TO 35' AGL/209' MSL. TREE 1079' FROM DER, 82' LEFT OF CENTERLINE, 35' AGL/214' MSL. OBSTUCTION LIGHT ON HOPPER 985' FROM DER, 353' RIGHT OF CENTERLINE, 72' AGL/236' MSL. BUSH 195' FROM DER, 364' LEFT OF CENTERLINE, 25' AGL/189' MSL. LIGHT POLE 1149' FROM DER, 160' LEFT OF CENTERLINE, 47' AGL/211' MSL. OBSTRUCTION LIGHT ON BUILDING 2289' FROM DER, 65' RIGHT OF CENTERLINE, 74' AGL/238' MSL.

QUALITY
1
CHECKED

City, State TRACY, CA		Airport TRACY MUNICIPAL		Effective Date 22 OCT 2009	Amdt. No. 3
DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date