

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 27										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH											
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: PKF NDB CLIMB TO 2600 THEN CLIMBING LEFT TURN TO 3200 DIRECT PKF NDB AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, LT, 336.44 INBOUND FAS OBST: 2013 TOWER 455256 / 902616 CHART: 3049 TOWER 455643 / 901623										
KRSMS INT			PKF NDB			284.50 / 17.24			4000												
RUSSH INT			PKF NDB			068.39 / 11.37			3200												
1. PT <u>R</u> SIDE OF COURSE <u>156.44</u> OUTBOUND <u>3200</u> FT WITHIN <u>10</u> MILES OF <u>PKF NDB</u> (IAF) 2. _____ 3. FAC <u>336.44</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: PKF NDB 360-360 4100										MAG VAR: 1W EPOCH YEAR: 00											
MINIMUMS																					
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15 FOR THIS AIRPORT						ALTERNATE: N		A		X					
CATEGORY		A			B			C			D			E							
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
S-36		2200	1	700	2200	1	700		NA			NA									
CIRCLING		2200	1	700	2200	1	700		NA			NA									
NOTES: USE PHILLIPS ALTIMETER SETTING. 																					
CITY AND STATE				ELEVATION: 1500 TDZE: 1500				FACILITY IDENTIFIER:				PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP					
PARK FALLS, WI				PARK FALLS MUNI				PKF				MAY 15 2003 NDB RWY 36, AMDT 1				AMDT ORIGINAL					
																DATED 22/01/99					