

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 14L, 14R, 32R STANDARD.

RWY 32L 300-1 ½ OR STANDARD WITH A MINIMUM CLIMB OF 250 FT PER NM TO 800.

(2) TEXTUAL DEPARTURE PROCEDURE:

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 32L, TREE, 1.24 NM FROM DER, 2285' LEFT OF CENTERLINE, 100' AGL/699' MSL. **NOTE: RWY 32R**, TREES BEGINNING 352' FROM DER, 198' LEFT OF CENTERLINE, UP TO 77' AGL/501' MSL. TREES BEGINNING 1349' FROM DER, 439' RIGHT OF CENTERLINE, UP TO 94' AGL/516' MSL.

(4) CONTROLLING OBSTACLES:

RWY 32L 699 MSL TREE 383345.00N/0895309.00W

QUALITY
2
CHECKED

(5) City, State

BELLEVILLE, IL

(6) Airport

SCOTT AFB, MID AMERICA

(7) Effective Date

29 JUL 2010

(8) Amdt. No.

ORIG