

FLIGHT STANDARDS SERVICES - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - ILS

NAVAID	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAD	DXO	K5011340VDHW	N42124729W083215998	N42124729W083215998W0060006372	NARDETROIT								
SUSAD	SVM	K5011430VTL	N42243109W083353805	N42243109W083353805W0030009561	NARSALEM								
SUSAD	KDTWK5	IBZB	K5011175 IT	IBZBN42115711W083230618	006430	NARDETROIT	METROPOLITAN	WAYNE	COU				

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KDTWK5FI22RY	AGRDCY	010GRDCYK5EA0E	A	IF			+ 07000	18000			0 NS	
SUSAP	KDTWK5FI22RY	AGRDCY	020MMOTRK5EA0E		TF			+ 06000				0 NS	
SUSAP	KDTWK5FI22RY	AGRDCY	030TAYULK5EA0E		TF			+ 05000				0 NS	
SUSAP	KDTWK5FI22RY	AGRDCY	040EMINNK5EA0E	B	TF			+ 04000				0 NS	
SUSAP	KDTWK5FI22RY	AGRDCY	050WONDRK5EA0EE		CF	IBZBK5	0322008921220030PI	+ 03000				0 NS	
SUSAP	KDTWK5FI22RY	I	010WONDRK5EA0E	I	IF	IBZBK5	03220089	PI	J	030000230018000		0 NS	
SUSAP	KDTWK5FI22RY	I	020JELVUK5EA0E	F	CF	IBZBK5	0322006821200021PI	H	0230002300	-300DXO	K5D	0 NS	
SUSAP	KDTWK5FI22RY	I	030CFBJNK5EA0EY	M	CF	IBZBK5	0322001821200050PI		00697	-300		0 NS	
SUSAP	KDTWK5FI22RY	I	040	0	M		2122	+ 01100				0 NS	
SUSAP	KDTWK5FI22RY	I	050	0	R	VIY	3310					0 NS	
SUSAP	KDTWK5FI22RY	I	060SVM	K5D	0VY	CF SVM	K5	0000000033500160D	+ 03000			0 NS	
SUSAP	KDTWK5FI22RY	I	070SVM	K5D	0VE	R	HM	2130T010	+ 03000			0 NS	

[illegible]

QUALITY
CHECKED

CITY AND STATE DETROIT, MI	ELEVATION: 645	THRE: 642	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			ILS Y RWY 22R, ORIG-B	AMDT: ORIG-A
	DETROIT METROPOLITAN WAYNE COUNTY		I-BZB	26 JULY 2012	DATED: 04/05/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

ILS STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except: HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3	
ILS	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012													

SUSAP	KDTWK5IIBZB1	011175RW22RN42115626W0832301932122N42132735W0832210301C10	10550364300W00605500638											

MSA	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012													

SUSAP	KDTWK5SDXO	K5D	0	18018002825										M



CITY AND STATE
DETROIT, MI

ELEVATION: 645 THRE: 642
AIRPORT NAME:
DETROIT METROPOLITAN WAYNE COUNTY

FACILITY
IDENTIFIER:
I-BZB

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
ILS Y RWY 22R, ORIG-B
26 JULY 2012

SUP:
AMDT: ORIG-A
DATED: 04/05/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

ILS STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - ILS

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	GRDCY	GRDCY	010	IAP	IF		FB				AA 07000	
	GRDCY	MMOTR	020		TF		FB				AA 06000	
	GRDCY	TAYUL	030		TF		FB				AA 05000	
	GRDCY	EMINN	040		TF		FB				AA 04000	
	GRDCY	WONDR	050		CF		FB		212.2()	003.0	AA 03000	
		WONDR	010	FACF	IF		FB				AA 03000	GI 02300
		JELVU	020	FAF	CF		FB		212.0()	002.1	GI 02300	GS 02300
		CFBJN	030	MAP	CF		FO		212.0()	005.0	AT 00697	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		212.2()		AA 01100	
		050		VI	R	FB		331.0()			
	SVM	060		CF		FO		335.0()	016.0	AA 03000	
	SVM	070		HM	R	FO		213.0()	001.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DXO	N421247.29	W0832159.98	N4212.788	W08322.000
	SVM	N422431.09	W0833538.05	N4224.518	W08335.634
	IBZB (DME)	N421157.11	W0832306.18	N4211.952	W08323.103
	CFBJN	N421333.98	W0832157.26	N4213.566	W08321.954
	EMINN	N422237.16	W0831556.84	N4222.619	W08315.947
	GRDCY	N423026.30	W0831043.97	N4230.438	W08310.733
	JELVU	N421801.34	W0831900.10	N4218.022	W08319.002
	MMOTR	N422752.28	W0831226.85	N4227.871	W08312.448
	TAYUL	N422515.93	W0831411.12	N4225.266	W08314.185
	WONDR	N421955.84	W0831744.08	N4219.931	W08317.735
	RW22R	N421334.48	W0832158.61	N4213.575	W08321.977
	IBZB (LOC)	N421156.26	W0832301.93	N4211.938	W08323.032

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW22R	00642	55

QUALITY
CHECKED

CITY AND STATE DETROIT, MI	ELEVATION: 645	THRE: 642	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: DETROIT METROPOLITAN WAYNE COUNTY		I-BZB	ILS Y RWY 22R, ORIG-B 26 JULY 2012	AMDT: ORIG-A
					DATED: 04/05/2012