

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.			
TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW29 CLIMB TO 3000 DIRECT DURBN AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 113.92 INBOUND. CHART FAS OBST: 1035 TREE 463819N/0965820W FIXER TO RW29: 3.00/40. CHART CIRCLING ICON			
FAR VORTAC	KENNT (FO)	155.51 / 12.75	3000				
RUSTD	COLFX (FB)	051.14 / 5.06	3000				
WIRDE (IAF)	KENNT (NOPT) (FB)	242.90 / 8.56	3000				
COLFX (IAF)	KENNT (NOPT) (FB)	024.23 / 5.50	3000				
KENNT (IF/IAF)	FIXER (FB)	294.28 / 6.02	2800				
FIXER (FAF)	AJBOF/3.20 NM TO RW29 (FB)	294.19 / 2.50					
(SEE FORM 8260-10)							

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)			
2. HOLD SE KENNT, LT, 294.28 INBOUND, 3000 FT. IN LIEU OF PT (IAF)			
3. FAC: <u>294.19</u> FAF: FIXER		DIST FAF TO MAP: <u>5.70</u> THLD: <u>5.70</u>	
4. MIN. ALT: KENNT 3000, FIXER 2800, AJBOF/3.20 NM TO RW29 2000			
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u>		150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u>		OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u> </u> TCH: 34:1 IS CLEAR			
8. MSA FROM: RW29 3200			

MINIMUMS			
TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>		ALTERNATE: N A <input type="checkbox"/> X <input type="checkbox"/>	
CATEGORY =====>	A		B
	DH/MDA	VIS	HAT/HAA
LNAV MDA	1340	1	393
CIRCLING	1680	1	733

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FAR VORTAC ON V344 NORTHBOUND AND V510 WESTBOUND.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 (SEE FORM 8260-10)

CITY AND STATE	ELEVATION: 947 TDZE: 947	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
KINDRED, ND	AIRPORT NAME:		RNAV (GPS) RWY 29, AMDT 1A	AMDT:
	ROBERT ODEGAARD FIELD		11 DECEMBER 2014	DATED 08/22/2013

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
AJBOF/3.20 NM TO RW29	RW29 (MAP) (FO)	294.19 / 3.20	
RW29 (MAP)	1340 MSL	294.19	
1340 MSL	DURBN (FO)		3000

NOTES, (CONT.):

CHART NOTE: NIGHT LANDING RWY 11 NA.

CHART NOTE: USE HECTOR INTL ALTIMETER SETTING.

QUALITY
4
CHECKED

CITY AND STATE

KINDRED, ND

ELEVATION: 947

TDZE: 947

AIRPORT NAME:

ROBERT ODEGAARD FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 29, AMDT 1A

11 DECEMBER 2014

SUP:

AMDT: 1

DATED: 08/22/2013

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

CITY AND STATE KINDRED, ND	ELEVATION: 947 AIRPORT NAME: ROBERT ODEGAARD FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 29, AMDT 1A 11 DECEMBER 2014	SUP: 4
				AMDT: 1
				DATED: 08/22/2013

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

Page 4 of 5 Pages

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	FAR	FAR	010		IF		FB					
	FAR	KENNT	020		TF		FO	2.0	155.5 (159.5T)	012.8	AA 03000	
	FAR	KENNT	030	IAF	HF	L	FO		294.3 (298.3T)	004.0	AA 03000	
	RUSTD	RUSTD	010		IF		FB					
	RUSTD	COLFX	020	IAF	TF		FB	2.0	051.1 (055.1T)	005.1	AA 03000	
	RUSTD	KENNT	030		TF		FB	1.0	024.2 (028.2T)	005.5	AA 03000	
	WIRDE	WIRDE	010	IAF	IF		FB					
	WIRDE	KENNT	020		TF		FB	1.0	242.9 (246.9T)	008.6	AA 03000	
		KENNT	010	FACF	IF		FB				AA 03000	
		FIXER	020	FAF	TF		FB	0.5	294.3 (298.3T)	006.0	AA 02800	
		AJBOF	021	SDF	TF		FB	0.3	294.2 (298.2T)	002.5	AA 02000	GS 02003
		RW29	030	MAP	TF		FO	0.3	294.2 (298.2T)	003.2	AT 00984	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		294.2 (298.2T)		AA 01340	
		DURBN	050		DF		FO				AA 03000	
		DURBN	060		HM	R	FO		113.9 (117.9T)	004.0	AA 03000	
POINT DATA		WAYPOINT		LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS		
		FAR		N464512.02		W0965104.74		N4645.200		W09651.079		
		AJBOF		N463717.29		W0965529.85		N4637.288		W09655.498		
		COLFX		N462825.12		W0964822.94		N4628.419		W09648.382		
		DURBN		N464415.68		W0971431.56		N4644.261		W09714.526		
		FIXER		N463606.42		W0965217.81		N4636.107		W09652.297		
		KENNT		N463315.69		W0964436.72		N4633.262		W09644.612		
		RUSTD		N462531.93		W0965423.20		N4625.532		W09654.387		
		WIRDE		N463637.70		W0963312.23		N4636.628		W09633.204		
		RW29		N463847.76		W0965935.57		N4638.796		W09659.593		
RUNWAY DATA			THRESHOLD									
		RWY	ELEVATION		TCH							
		RW29	00944		40							

CITY AND STATE KINDRED, ND	ELEVATION: 947	TDZE: 947	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: ROBERT ODEGAARD FIELD		RNAV	RNAV (GPS) RWY 29, AMDT 1A 11 DECEMBER 2014	4
					AMDT: CHECKED
					DATED: 08/22/2013