

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
RUGBY, ND	RUGBY MUNI	24 JULY 2014	1

TAKEOFF MINIMUMS:

RWY 30, STANDARD.

RWY 12, 300 – 1 3/4 OR STANDARD WITH MINIMUM CLIMB OF 300 FT PER NM TO 2000.

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 12, TREES BEGINNING 1186 FT FROM DER, 432 FT LEFT OF CENTERLINE, UP TO 67 FT AGL/1620 FT MSL. ELEVATORS BEGINNING 1.4 NM FROM DER, 819 FT RIGHT OF CENTERLINE, UP TO 246 FT AGL/1804 FT MSL.

NOTE: RWY 30, EDGE LIGHT 11 FT FROM DER, 9 FT RIGHT OF CENTERLINE, 1 FT AGL/1534 FT MSL. EDGE LIGHT 11 FT FROM DER, 20 FT LEFT OF CENTERLINE, 1 FT AGL/1534 FT MSL.

CONTROLLING OBSTACLES:

RWY 12: 1785 FT MSL ELEVATOR 482213.51N/0995931.66W, 1804 FT MSL ELEVATOR 482213.45N/0995935.10W.



U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
RUGBY, ND	RUGBY MUNI	24 JULY 2014	1

REMARKS:

FLIGHT INSPECTED BY:

Paul Koscheka *[Signature]* 5-16-11

REQUIRED EFFECTIVE DATE:

ROUTINE

DEVELOPED BY:

STEVEN NELSON *[Signature]* AJV-353

03/10/2014

APPROVED BY:

GEORGE GONZALEZ *[Signature]*
MANAGER AJV-353

430.14

COORDINATED WITH:

ALPA, AOPA, NBAA, ZMP, AMGR

CHANGES:

1. CHANGED TAKEOFF MINIMUMS: RWY 12 FROM STANDARD TO 300 – 1 3/4 OR STANDARD WITH MINIMUM CLIMB OF 300 FT PER NM TO 2000.
2. UPDATED TAKEOFF OBSTACLE NOTES.
3. ADDED CONTROLLING OBSTACLES: RWY 12: 1785 FT MSL ELEVATOR 482213.51N/0995931.66W, 1804 FT MSL ELEVATOR 482213.45N/0995935.10W.

REASONS:

- 1 – 3. REFLECTS CURRENT AIRPORT DATA AND DATABASE OBSTACLES.